




with transparent bowl and guard



Wilkerson Combination Units D18

Features:

- light weight, Ready-to-Mount assembly comes standard with pressure gauge and modular T-Bracket/Joiner Assembly
- components integrated into single unit
- modern design and appearance
- quick disconnect bowl / bowl guard
- maximum operating conditions:
 - transparent bowl: **150 PSIG** (10.3 bar) and **32°F to 125°F (0°C to 52°C)**
 - metal bowl: **250 PSIG** (17.2 bar) and **32°F to 150°F (0°C to 66°C)**
- 5 micron element
- 4.09 oz. bowl/lubricator

Regulator

- 0-125 PSI adjusting range
- self-relieving
- supplied with gauge
- 1.72 oz. bowl/filter


Size	Flow (SCFM)	With Transparent Bowl and Guard		With Metal Bowl / Sight Gauge	
		Manual Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/2"	150	D18-04M	\$331.30	D18-04MMB	\$339.25

SCFM ratings at 150 PSIG inlet pressure.

Wilkerson Combination Units D28



with metal bowl



Features:

- light weight, Ready-to-Mount assembly comes standard with pressure gauge and modular T-Bracket/Joiner Assembly
- components integrated into single unit
- modern design and appearance
- quick disconnect bowl / bowl guard
- maximum operating conditions:
 - **250 PSIG** (17.2 bar) and **32°F to 150°F (0°C to 66°C)**
- 5 micron element
- 6.11 oz. bowl/lubricator

Regulator

- 0-125 PSI adjusting range
- self-relieving
- supplied with gauge
- 2.87 oz. bowl/filter

Size	Flow (SCFM)	With Metal Bowl / Sight Gauge	
		Manual Drain	
		Part #	Price/E
1/2"	110	D28-04MMB	\$406.15
3/4"	175	D28-06MMB	406.15



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings given at 150 PSIG inlet pressure.