

DF-Series Pneumatic Couplings

Features:


- pressure ratings: brass coupler / steel plug: **500 PSI**, brass coupler / brass plug: **300 PSI**, steel coupler / steel plug: **500 PSI**, 303 stainless steel coupler / 303 stainless steel plug: **500 PSI**
- temperature range: **-40°F to 250°F (-40°C to 121°C)**
- interchanges with other Industrial Interchange designs
- interchanges with the MIL-C-4109, A-A 59439, and ISO6150B standards

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure. For safety check valves and cables see pages G-46 and I-26.




Female Thread Plugs

Body Size	Threads	Brass			Steel		303 Stainless Steel		
		Previous Part #	Part #	Price/E	Part #	Price/E	Previous Part #	Part #	Price/E
1/4"	1/8" - 27 NPTF	---	---	---	D2F1	\$3.45	---	---	---
	1/4" - 18 NPTF	DCP20B	D2F2-B	\$3.41	D2F2	2.16	DCP20S	D2F2-S	\$11.58
	1/4" - 19 BSPP	---	---	---	D2BF2	3.55	---	---	---
	3/8" - 18 NPTF	DCP2023B	D2F3-B	5.23	D2F3	3.63	---	D2F3-S	12.58
	3/8" - 19 BSPP	---	---	---	D2BF3	4.93	---	---	---
3/8"	1/4" - 18 NPTF	---	---	---	D3F2	4.97	---	---	---
	3/8" - 18 NPTF	---	D3F3-B	6.82	D3F3	4.33	DCP26S	D3F3-S	26.32
	3/8" - 19 BSPP	---	---	---	D3BF3	4.97	---	---	---
	1/2" - 14 NPTF	---	---	---	D3F4	7.89	---	---	---
	3/8" - 18 NPTF	---	---	---	D4F3	7.60	---	---	---
1/2"	1/2" - 14 NPTF	---	D4F4-B	8.87	D4F4	7.31	DCP18S	D4F4-S	28.65
	1/2" - 14 BSPP	---	---	---	D4BF4	7.60	---	---	---
	3/4" - 14 NPTF	---	D4F6-B	14.89	D4F6	12.86	---	---	---
	1/2" - 14 NPTF	---	---	---	D6F4	15.05	---	---	---
3/4"	3/4" - 14 NPTF	---	---	---	D6F6	15.94	---	---	---
	1" - 11 1/2 NPTF	---	---	---	D6F8	25.28	---	---	---



brass



steel



303 stainless



Male Thread Plugs

Body Size	Threads	Brass			Steel		303 Stainless Steel		
		Previous Part #	Part #	Price/E	Part #	Price/E	Previous Part #	Part #	Price/E
1/4"	1/8" - 27 NPTF	DCP2101B	D2M1-B	\$3.64	D2M1	\$2.75	---	D2M1-S	\$12.58
	1/4" - 18 NPTF	DCP21B	D2M2-B	2.39	D2M2	2.10	DCP21S	D2M2-S	9.13
	1/4" - 19 BSPT	---	---	---	D2BM2	2.83	---	---	2.83
	3/8" - 18 NPTF	DCP2103B	D2M3-B	4.54	D2M3	3.16	---	D2M3-S	12.58
	3/8" - 19 BSPT	---	---	---	D2BM3	3.62	---	---	3.62
3/8"	1/4" - 18 NPTF	---	---	---	D3M2	3.56	---	---	3.56
	3/8" - 18 NPTF	---	D3M3-B	5.85	D3M3	3.51	DCP25S	D3M3-S	18.72
	3/8" - 19 BSPT	---	---	---	D3BM3	4.91	---	---	4.91
	1/2" - 14 NPTF	---	---	---	D3M4	7.01	---	---	7.01
	1/4" - 18 NPTF	---	---	---	D4M2	6.96	---	---	6.96
1/2"	3/8" - 18 NPTF	---	---	---	D4M3	5.73	---	---	5.73
	1/2" - 14 NPTF	---	D4M4-B	9.21	D4M4	5.85	DCP17S	D4M4-S	28.65
	1/2" - 14 BSPT	---	---	---	D4BM4	7.54	---	---	7.54
	3/4" - 14 NPTF	---	D4M6-B	13.24	D4M6	10.76	---	---	10.76
3/4"	1/2" - 14 NPTF	---	---	---	D6M4	13.54	---	---	13.54
	3/4" - 14 NPTF	---	---	---	D6M6	13.54	---	---	13.54
	1" - 11 1/2 NPTF	---	---	---	D6M8	15.05	---	---	15.05



brass



steel



303 stainless