Air Chief Automotive Interchange Quick-Connect Couplers

Features:

- pressure rating: 300 PSI
- temperature range: -40°F to 250°F
- interchanges with popular makes of automotive quick-connect fittings such as Amflo, Dill, Milton and Truflate, some makes
 do not interchange with any others, if you plan to interchange these couplings make sure you have plug ends with the proper
 configuration

Female Pipe Thread

Body Size	Female NPT	Material	Flow Rating at 100 PSI	Part #	Price/E	Opt Qty
1/4"	1/8"	brass	37 CFM	DC221	\$14.95	25
1/4"	1/4"	brass	37 CFM	DC2	10.85	25
1/4"	3/8"	brass	37 CFM	DC223	15.00	10
3/8"	1/4"	steel	70 CFM	DC8	22.70	10
3/8"	3/8"	steel	70 CFM	DC6	22.10	10
3/8"	1/2"	steel	70 CFM	DC624	30.50	10
1/2"	3/8"	steel	150 CFM	DC1023	32.60	10
1/2"	1/2"	steel	150 CFM	DC10	30.55	10
1/2"	3/4"	steel	150 CFM	DC1026	40.15	10

semi-automatic pull sleeve to connect



Male Pipe Thread

Body Size	Male NPT	Material	Flow Rating at 100 PSI	Part #	Price/E	Opt Qty
1/4"	1/8"	brass	37 CFM	DC101	\$13.85	10
1/4"	1/4"	brass	37 CFM	DC1	10.80	10
1/4"	3/8"	brass	37 CFM	DC103	13.80	10
3/8"	1/4"	steel	70 CFM	DC7	22.65	10
3/8"	3/8"	steel	70 CFM	DC5	22.05	10
3/8"	1/2"	steel	70 CFM	DC504	26.50	10
1/2"	3/8"	steel	150 CFM	DC903	30.60	10
1/2"	1/2"	steel	150 CFM	DC9	26.90	10
1/2"	3/4"	steel	150 CFM	DC906	36.15	10

semi-automatic pull sleeve to connect



Standard Hose Barb

Body Size	Hose ID	Material	Flow Rating at 100 PSI	Part #	Price/E	Opt Qty
1/4"	1/4"	brass	37 CFM	DC242	\$14.40	10
1/4"	5/16"	brass	37 CFM	DC243	11.60	10
1/4"	3/8"	brass	37 CFM	DC244	14.70	10
3/8"	1/4"	steel	70 CFM	DC642	26.25	10
3/8"	3/8"	steel	70 CFM	DC644	23.50	10
3/8"	1/2"	steel	70 CFM	DC645	26.00	10
1/2"	3/8"	steel	150 CFM	DC1044	34.90	10
1/2"	1/2"	steel	150 CFM	DC1045	32.75	10
1/2"	3/4"	steel	150 CFM	DC1046	34.60	10

semi-automatic pull sleeve to connect



Push-On Hose Barb

Body Size	Hose ID	Material	Flow Rating at 100 PSI	Part #	Price/E	Opt Qty
1/4"	1/4"	brass	37 CFM	DC242L	\$14.40	25
1/4"	3/8"	brass	37 CFM	DC244L	14.70	25
3/8"	1/4"	steel	70 CFM	DC642L	37.40	25
3/8"	3/8"	steel	70 CFM	DC644L	25.75	25

semi-automatic pull sleeve to connect

