



## Mann Tek Dry Disconnects for Steam Service

### Applications:

- designed to fit hoses carrying steam used in chemical (heating), pharmaceutical (disinfection and sterilization) and at loading bays

### Features:

- coupling housing and all inner parts: stainless steel
- EPDM 291 seal
- unintentional separation is eliminated preventing accidents and avoiding unintended down time
- performance unaffected by surface rust
- lockable versions are available on 1½" and 2", contact Dixon®
- couplers supplied with double handles
- 150 PSI at 350°F (177°C)**

### Coupler - Hose Unit x Female NPT

| Female NPT | Body Size | 316 Stainless Steel |                  |
|------------|-----------|---------------------|------------------|
|            |           | Part #              | Price/E          |
| ¾"         | 56 mm     | <b>DDSC075SS</b>    | <b>\$2423.05</b> |
| 1"         | 56 mm     | <b>DDSC100SS</b>    | <b>2423.05</b>   |
| 1½"        | 70 mm     | <b>DDSC150SS</b>    | <b>2833.35</b>   |
| 2"         | 70 mm     | <b>DDSC200SS</b>    | <b>2833.35</b>   |



### Adapter - Tank Unit x Female NPT

| Female NPT | Body Size | 316 Stainless Steel |                 |
|------------|-----------|---------------------|-----------------|
|            |           | Part #              | Price/E         |
| ¾"         | 56 mm     | <b>DDSA075SS</b>    | <b>\$745.50</b> |
| 1"         | 56 mm     | <b>DDSA100SS</b>    | <b>745.50</b>   |
| 1½"        | 70 mm     | <b>DDSA150SS</b>    | <b>982.20</b>   |
| 2"         | 70 mm     | <b>DDSA200SS</b>    | <b>982.20</b>   |

