

## Fiberglass Sleeving

**Features:**



- Braided texturized fiberglass tubing provides thermal insulation protection in applications with service temperatures up to **1000°F**.
- supplied in a continuous length of 100'

- 1/16" wall thickness
- braided from texturized E-glass filament yarns. The untreated tubing is flexible and expands to cover changing diameters.



Nominal ID	Part #	Price/E	Nominal ID	Part #	Price/E
1/4"	<b>LW04200</b>	<b>\$81.25</b>	1 1/4"	<b>LW20200</b>	<b>\$220.25</b>
3/8"	<b>LW06200</b>	<b>81.25</b>	1 1/2"	<b>LW24200</b>	<b>318.70</b>
1/2"	<b>LW08200</b>	<b>127.50</b>	2"	<b>LW32200</b>	<b>371.00</b>
5/8"	<b>LW10200</b>	<b>129.50</b>	2 1/2"	<b>LW40200</b>	<b>399.75</b>
3/4"	<b>LW12200</b>	<b>139.00</b>	3"	<b>LW48200</b>	<b>434.60</b>
7/8"	<b>LW14200</b>	<b>156.40</b>	3 1/2"	<b>LW56200</b>	<b>521.50</b>
1"	<b>LW16200</b>	<b>214.50</b>	4"	<b>LW64200</b>	<b>539.00</b>

## Nylon Protective Sleeves - MSHA Accepted



**Features:**

- woven tubular sleeving, ideal for use as a protective covering on hydraulic and industrial hose
- tight weave of seamless tubular sleeving helps dispense the flow of fluid in a ruptured hose
- MSHA accepted, withstands temperatures up to **275°F** (135°C) and fully passes flammability tests

Nominal ID	Outside Flat	100' rolls		300' rolls	
		Part #	Price/E	Part #	Price/E
0.90"	1.50"	<b>DHS90-100</b>	<b>\$142.35</b>	<b>DHS90-300</b>	<b>\$388.20</b>
1.00"	1.66"	<b>DHS100-100</b>	<b>152.90</b>	<b>DHS100-300</b>	<b>417.00</b>
1.13"	1.88"	<b>DHS106-100</b>	<b>164.10</b>	<b>DHS106-300</b>	<b>447.40</b>
1.25"	2.13"	<b>DHS122-100</b>	<b>186.95</b>	<b>DHS122-300</b>	<b>509.85</b>
1.46"	2.25"	<b>DHS138-100</b>	<b>212.95</b>	<b>DHS138-300</b>	<b>580.70</b>
1.42"	2.50"	<b>DHS142-100</b>	<b>218.35</b>	<b>DHS142-300</b>	<b>595.45</b>
1.58"	2.75"	<b>DHS159-1-100</b>	<b>226.10</b>	<b>DHS159-1-300</b>	<b>616.55</b>
1.78"	2.88"	<b>DHS175-100</b>	<b>248.25</b>	<b>DHS175-300</b>	<b>677.00</b>
1.91"	3.00"	<b>DHS181-100</b>	<b>262.00</b>	<b>DHS181-300</b>	<b>714.50</b>
2.18"	3.63"	<b>DHS219-100</b>	<b>330.60</b>	<b>DHS219-300</b>	<b>901.70</b>
2.38"	3.88"	<b>DHS238-100</b>	<b>392.55</b>	<b>DHS238-300</b>	<b>1070.45</b>
2.65"	4.25"	<b>DHS263-100</b>	<b>418.55</b>	<b>DHS263-300</b>	<b>1141.50</b>
2.86"	4.75"	<b>DHS288-100</b>	<b>461.15</b>	<b>DHS288-300</b>	<b>1257.65</b>
3.65"	5.88"	<b>DHS366-100</b>	<b>550.05</b>	<b>DHS366-300</b>	<b>1500.00</b>

## Spring Guard



with tang



without tang

**Features:**

- protects hose against the effects of flexing at its most vulnerable point - immediately behind the coupling
- optional end tang allows end guard to be secured under a clamp or ferrule
- wire fits most hose OD's from 1/2" to 3 1/4", contact Dixon for custom sizes or lengths

Guard ID	Wire Gauge	Overall Length	Tang Length	Approx. # of Coils per Foot	Galvanized Steel with Tang		304 Stainless Steel with Tang		Galvanized Steel without Tang		304 Stainless Steel without Tang	
					Part #	Price/E	Part #	Price/E	Part #	Price/E	Part #	Price/E
3/4"	0.175	12"	1"	33	<b>SEGC1-0.75-12</b>	<b>\$14.00</b>	<b>SEGS1-0.75-12</b>	<b>\$18.00</b>	<b>SEGC0-0.75-12</b>	<b>\$10.00</b>	<b>SEGS0-0.75-12</b>	<b>\$17.00</b>
1"	0.175	12"	1"	33	<b>SEGC1-1.00-12</b>	<b>16.00</b>	<b>SEGS1-1.00-12</b>	<b>24.00</b>	<b>SEGC0-1.00-12</b>	<b>12.00</b>	<b>SEGS0-1.00-12</b>	<b>20.00</b>
1 1/4"	0.175	14"	2"	39	<b>SEGC1-1.25-14</b>	<b>17.00</b>	<b>SEGS1-1.25-14</b>	<b>26.00</b>	<b>SEGC0-1.25-14</b>	<b>13.00</b>	<b>SEGS0-1.25-14</b>	<b>21.00</b>
1 1/2"	0.175	14"	2"	39	<b>SEGC1-1.50-14</b>	<b>18.00</b>	<b>SEGS1-1.50-14</b>	<b>27.00</b>	<b>SEGC0-1.50-14</b>	<b>14.00</b>	<b>SEGS0-1.50-14</b>	<b>23.00</b>
1 3/4"	0.175	16"	2"	44	<b>SEGC1-1.75-16</b>	<b>21.00</b>	<b>SEGS1-1.75-16</b>	<b>31.00</b>	<b>SEGC0-1.75-16</b>	<b>18.00</b>	<b>SEGS0-1.75-16</b>	<b>27.00</b>
2"	0.280	16"	2"	44	<b>SEGC1-2.00-16</b>	<b>24.00</b>	<b>SEGS1-2.00-16</b>	<b>32.00</b>	<b>SEGC0-2.00-16</b>	<b>21.00</b>	<b>SEGS0-2.00-16</b>	<b>28.00</b>
2 1/2"	0.280	18"	2"	50	<b>SEGC1-2.50-18</b>	<b>25.00</b>	<b>SEGS1-2.50-18</b>	<b>40.00</b>	<b>SEGC0-2.50-18</b>	<b>22.00</b>	<b>SEGS0-2.50-18</b>	<b>36.00</b>
3"	0.280	18"	2"	50	<b>SEGC1-3.00-18</b>	<b>30.00</b>	<b>SEGS1-3.00-18</b>	<b>42.00</b>	<b>SEGC0-3.00-18</b>	<b>27.00</b>	<b>SEGS0-3.00-18</b>	<b>38.00</b>

## Continuous Spring Guard

**Features:**

- protects hose from external abrasion and helps resist over flexing
- fits tight to hose reducing the potential for snagging
- contact Dixon for custom lengths or sizes



Guard ID	Wire Gauge	Overall Length	Approx. # of Coils per Foot	Galvanized Steel		304 Stainless Steel	
				Part #	Price/E	Part #	Price/E
3/4"	0.175	25'	33	<b>CWG-C-0.75-25</b>	<b>\$98.00</b>	<b>CWG-S-0.75-25</b>	<b>\$380.25</b>
1"	0.175	25'	33	<b>CWG-C-1.00-25</b>	<b>168.25</b>	<b>CWG-S-1.00-25</b>	<b>433.25</b>
1 1/4"	0.175	25'	33	<b>CWG-C-1.25-25</b>	<b>168.25</b>	<b>CWG-S-1.25-25</b>	<b>433.25</b>
1 1/2"	0.175	25'	33	<b>CWG-C-1.50-25</b>	<b>230.50</b>	<b>CWG-S-1.50-25</b>	<b>526.00</b>
1 3/4"	0.175	25'	33	<b>CWG-C-1.75-25</b>	<b>230.50</b>	<b>CWG-S-1.75-25</b>	<b>526.00</b>
2"	0.280	25'	33	<b>CWG-C-2.00-25</b>	<b>327.25</b>	<b>CWG-S-2.00-25</b>	<b>628.00</b>
2 1/2"	0.280	25'	33	<b>CWG-C-2.50-25</b>	<b>420.00</b>	<b>CWG-S-2.50-25</b>	<b>720.75</b>
3"	0.280	25'	33	<b>CWG-C-3.00-25</b>	<b>522.00</b>	<b>CWG-S-3.00-25</b>	<b>804.25</b>