


Straight Through Quick-Connect Fittings

Features:

- no internal valves, which provide maximum flow with minimum pressure drop
- interchanges with Parker-Hannifin SST/BST, Foster FST and Hansen ST couplings, see Hydraulic Profile Chart on page 833.
- **Do Not Disconnect with pressure in line.** 

Female Plugs

Body Size	NPTF Thread	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/4" - 18	5500	steel	STFP2	\$2.77	12
3/8"	3/8" - 18	4500	steel	STFP3	4.37	12
1/2"	1/2" - 14	3500	steel	STFP4	6.14	12
3/4"	3/4" - 14	3100	steel	STFP6	14.18	12
1"	1" - 11 1/2	2500	steel	STFP8	26.57	1
1 1/4"	1 1/4" - 11 1/2	2500	steel	STFP10	61.97	1
1 1/2"	1 1/2" - 11 1/2	2500	steel	STFP12	99.62	1
2"	2" - 11 1/2	2500	steel	STFP16	127.42	1
1/4"	1/4" - 18	3800	brass	STFP2B	5.20	12
3/8"	3/8" - 18	2700	brass	STFP3B	6.60	12
1/2"	1/2" - 14	2200	brass	STFP4B	9.85	12
3/4"	3/4" - 14	1700	brass	STFP6B	15.60	12
1"	1" - 11 1/2	1200	brass	STFP8B	29.25	1
1 1/4"	1 1/4" - 11 1/2	1800	brass	E10F10-B	54.03	10
1 1/2"	1 1/2" - 11 1/2	1800	brass	E12F12-B	87.79	5
2"	2" - 11 1/2	1800	brass	E16F16-B	119.31	1
1/4"	1/4" - 18	6700	303 stainless	STFP2SS	17.80	5
3/8"	3/8" - 18	5500	303 stainless	STFP3SS	20.75	5
1/2"	1/2" - 14	3000	303 stainless	STFP4SS	47.00	5
3/4"	3/4" - 14	3000	303 stainless	STFP6SS	71.10	5
1"	1" - 11 1/2	1700	303 stainless	STFP8SS	128.50	5
1 1/4"	1 1/4" - 11 1/2	2000	303 stainless	E10F10-S	139.00	10
1 1/2"	1 1/2" - 11 1/2	2000	303 stainless	E12F12-S	243.25	5
2"	2" - 11 1/2	2000	303 stainless	E16F16-S	312.74	1



H

Male Plugs

Body Size	NPTF Thread	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/4" - 18	5500	steel	STMP2	\$2.77	12
3/8"	3/8" - 18	4500	steel	STMP3	4.37	12
1/2"	1/2" - 14	3500	steel	STMP4	6.14	12
3/4"	3/4" - 14	3100	steel	STMP6	14.18	12
1"	1" - 11 1/2	2500	steel	STMP8	26.57	1
1 1/4"	1 1/4" - 11 1/2	2500	steel	STMP10	69.50	1
1 1/2"	1 1/2" - 11 1/2	2500	steel	STMP12	99.62	1
2"	2" - 11 1/2	2500	steel	STMP16	133.20	1
1/4"	1/4" - 18	3800	brass	STMP2B	4.85	12
3/8"	3/8" - 18	2700	brass	STMP3B	6.00	12
1/2"	1/2" - 14	2200	brass	STMP4B	9.30	12
3/4"	3/4" - 14	1700	brass	STMP6B	13.70	12
1"	1" - 11 1/2	1600	brass	STMP8B	27.00	1
1 1/4"	1 1/4" - 11 1/2	1800	brass	E10M10-B	61.91	10
1 1/2"	1 1/2" - 11 1/2	1800	brass	E12M12-B	87.79	5
2"	2" - 11 1/2	1800	brass	E16M16-B	120.43	1
1/4"	1/4" - 18	6700	303 stainless	STMP2SS	15.90	5
3/8"	3/8" - 18	5500	303 stainless	STMP3SS	18.00	5
1/2"	1/2" - 14	3000	303 stainless	STMP4SS	43.00	5
3/4"	3/4" - 14	3000	303 stainless	STMP6SS	67.00	5
1"	1" - 11 1/2	1700	303 stainless	STMP8SS	136.50	5



Standard Hose Barb Plugs ¹

Body Size	Hose ID	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/4"	3800	brass	E2S2-B	\$5.16	100
3/8"	3/8"	2800	brass	E3S3-B	6.32	50
1/2"	1/2"	2200	brass	E4S4-B	12.05	25
3/4"	3/4"	1700	brass	E6S6-B	15.78	20
1"	1"	1700	brass	E8S8-B	34.43	10
1/4"	1/4"	5200	steel	E2S2	6.03	100
3/8"	3/8"	2800	steel	E3S3	7.80	50
1/2"	1/2"	2200	steel	E4S4	14.65	25
3/4"	3/4"	1700	steel	E6S6	18.53	20
1"	1"	1700	steel	E8S8	37.07	10



¹ Operating pressures for the standard hose barbs utilizing hose barb end connections may be dramatically reduced to that of the hose rating and/or hose and end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.