

Global Brass Ball Valves

Applications:

- for water and air only

Features:

- pressure ratings:
 - 1/4" - 3/8" rated to **365 PSI**
 - 1/2" - 2" rated to **600 PSI**
- forged brass body
- maximum temperature: **248°F (120°C)**



female NPT x female NPT

Size	Port	Brass	
		Part #	Price/E
1/4"	full	FBVG25	\$7.50
3/8"	full	FBVG38	7.50
1/2"	full	FBVG50	11.80
3/4"	full	FBVG75	16.60
1"	full	FBVG100	27.25
1 1/4"	full	FBVG125	42.00
1 1/2"	full	FBVG150	59.00
2"	full	FBVG200	90.00

Solder End Brass Ball Valves

Application:

- designed to provide the best protection against potential gas leakage under extreme duty or low pressure applications

Features:

- pressure rating: **600 PSI WOG**; **150 PSI** working steam pressure
- maximum temperature: **366°F**
- Underwriters Listed
- brass body
- blow-out proof stem
- chrome-plated brass ball
- adjustable stem packing nut
- PTFE seat, seal, and thrust washer



Size	Port	Brass	
		Part #	Price/E
1/2"	full	FBV50SE	\$23.95
3/4"	full	FBV75SE	32.65
1"	full	FBV100SE	48.15
1 1/4"	full	FBV125SE	86.80
1 1/2"	full	FBV150SE	125.55
2"	full	FBV200SE	178.15

2014
NEW

Lead Free Brass Ball Valves

Features:

- lead free refers to the wetted surface of pipes, fittings and fixtures in potable water systems that have a weighted average lead content = 0.25%. Source: California Health & Safety Code (116875). Vermont Act 193*171NLF
- pressure rating: 600 WOG - 150 WSP
- maximum temperature: **366°F**
- PTFE seat and double O-ring stem packing



Size	Port	Brass	
		Part #	Price/E
1/2"	full	LFV50	\$26.75
3/4"	full	LFV75	38.00
1"	full	LFV100	57.00
1 1/4"	full	LFV125	99.00
1 1/2"	full	LFV150	146.00
2"	full	LFV200	206.00