

Butterfly Valves

Storz x Female Swivel

Features:

- permits safe controlled flow to the intake pump, can be used for draft situations
- pressure range: **150-300 PSI** working pressure at **70°F (21°C)**
- water way: 4½", 5", and 6" maximum
- materials: body-ASTN A-126 cast iron, wafer-lightweight aluminum cast 356-T6, , seat - Buna
- ¾" push-pull drain valve
- standard 10-position locking style lever
- finish anodized cast aluminum bolt flanges - minimum thickness 0.001"
- lever handle to center valve is 10¼"
- can be used in either direction (e.g. inlet/outlet)

Valves



Storz	Female NST (NH) Swivel	Length	Width	Height	ASTN A-126 Cast Iron	
					Part #	Price/E
4"	4"	9½"	11"	18"	SFBTFLY4040F	\$3234.80
	4½"	9½"	11"	18"	SFBTFLY4045F	3055.40
	5"	9½"	11"	18"	SFBTFLY4050F	3109.35
	6"	9½"	11"	18"	SFBTFLY4060F	2980.70
5"	4"	9½"	11"	18"	SFBTFLY5040F	3115.00
	4½"	9½"	11"	18"	SFBTFLY5045F	2945.00
	5"	9½"	11"	18"	SFBTFLY5050F	2997.10
6"	6"	9½"	11"	18"	SFBTFLY5060F	2868.50
	6"	9½"	13"	18"	SFBTFLY6060F	3016.40

L/H - Male x Female Swivel

Features:

- permits safe controlled flow to the intake pump, can be used for draft situations
- standard 10 position lever handle
- ¾" push-pull drain valve standard
- pressure range: **150-300 PSI** at **70°F (21°C)**
- water way: 4½", 5", and 6" maximum
- seat: Buna
- finish: anodized cast aluminum bolt flanges (minimum thickness 0.001")
- lever handle to center valve is 10¼", unit can be used in either direction e.g. inlet/outlet



Male NST (NH)	Female NST (NH) Swivel	Length	Width	Height	ASTN A-126 Cast Iron	
					Part #	Price/E
4"	4"	9½"	11"	18"	FMBTFLY40F40F	\$1920.50
4"	4½"	9½"	11"	18"	FMBTFLY40F45F	1920.50
4"	6"	9½"	11"	18"	FMBTFLY40F60F	2839.05
4½"	4½"	9½"	11"	18"	FMBTFLY45F45F	2561.65
5"	4½"	9½"	11"	18"	FMBTFLY50F45F	2809.40
5"	5"	9½"	11"	18"	FMBTFLY50F50F	2879.35
5"	6"	9½"	11"	18"	FMBTFLY50F60F	2731.05
6"	6"	9½"	13"	18"	FMBTFLY60F60F	2552.15