Global Cam and Groove

Features:

- interchange with all products produced to A-A-59326D
- made to Dixon specifications and branded Dixon
- Buna seals are standard
- pressure rating for adapters is based on the seal of the mating part



Dust caps and dust plugs are not to be used in pressure applications for safety and environmental reasons

Global Type A Adapters

Size	A380 Permanent Mold AL		ASTMC38000 F	orged Brass	316 Investment Cast SS		
	Part #	Price/E	Part #	Price/E	Part #	Price/E	
1/2"	G50-A-AL 1	\$6.35	G50-A-BR 1	\$11.80	G50-A-SS N	W \$18.00	
3/4"	G75-A-AL	5.00	G75-A-BR	10.70	G75-A-SS	19.00	
1"	G100-A-AL	5.10	G100-A-BR	13.70	G100-A-SS	18.60	
11/4"	G125-A-AL	7.75	G125-A-BR	17.70	G125-A-SS	29.10	
11/2"	G150-A-AL	5.70	G150-A-BR	20.45	G150-A-SS	31.05	
2"	G200-A-AL	6.05	G200-A-BR	26.70	G200-A-SS	37.45	
21/2"	G250-A-AL	14.60	G250-A-BR	41.05	G250-A-SS	72.30	
3"	G300-A-AL	12.40	G300-A-BR	47.05	G300-A-SS	78.35	
4"	G400-A-AL	19.55	G400-A-BR	82.80	G400-A-SS	138.35	
5"	G500-A-AL 1	73.60	G500-A-BR1	197.30			
6"	G600-A-AL	51.40			G600-A-SS	248.50	
8"	G800-A-AL 1	238.55					



female NPT x male adapter

Global Type B Couplers

	A380 Permanent Mold		ASTMC38000 Forged		316 Investment Cast		A380 Permanent Mold	
Size	AL with Brass Handles		Brass		Stainless Steel		AL with SS Handles	
	Part #	Price/E	Part #	Price/E	Part #	√Price/E	Part #	Price/E
1/2"	G50-B-AL ^{1,2}	\$16.20	G50-B-BR1	\$27.10	G50-B-SS	\$29.50		
3/4"	G75-B-AL ²	10.75	G75-B-BR	24.45	G75-B-SS	31.45		
1"	G100-B-AL	11.95	G100-B-BR	26.35	G100-B-SS	32.20		
11/4"	G125-B-AL	16.30	G125-B-BR	36.70	G125-B-SS	52.45		
11/2"	G150-B-AL	13.65	G150-B-BR	35.70	G150-B-SS	52.10	G150-B-ALSI	\$13.65
2"	G200-B-AL	14.25	G200-B-BR	41.90	G200-B-SS	65.55	G200-B-ALSI	14.25
21/2"	G250-B-AL	26.00	G250-B-BR	63.35	G250-B-SS	94.60		
3"	G300-B-AL	23.60	G300-B-BR	77.70	G300-B-SS	109.35	G300-B-ALSI	23.60
4"	G400-B-AL	33.35	G400-B-BR	108.85	G400-B-SS	160.40	G400-B-ALSI	33.35
5"	G500-B-AL1	97.05	G500-B-BR1	316.10				
6"	G600-B-AL	92.70			G600-B-SS	429.75		



female coupler x male NPT

Global Type C Couplers

	A380 Permanent Mold		ASTMC38000 Forged		316 Investment Cast		A380 Permanent Mold	
Size	AL with Brass Handles		Brass		SS		AL with SS Handles	
	Part #	Price/E	Part #	Price/E	Part #	Price/E	Part #	Price/E
1/2"	G50-C-AL 1,2	\$13.15	G50-C-BR1	\$31.10	G50-C-SS	["] \$28.75		
3/4"	G75-C-AL ²	10.70	G75-C-BR	20.40	G75-C-SS	30.40		
1"	G100-C-AL	10.95	G100-C-BR	29.50	G100-C-SS	29.50		
11/4"	G125-C-AL	15.50	G125-C-BR	30.25	G125-C-SS	50.35		
11/2"	G150-C-AL	13.20	G150-C-BR	39.60	G150-C-SS	49.80	G150-C-ALSI	\$13.20
2"	G200-C-AL	15.25	G200-C-BR	48.05	G200-C-SS	63.65	G200-C-ALSI	15.25
21/2"	G250-C-AL	25.90	G250-C-BR	70.45	G250-C-SS	86.00		
3"	G300-C-AL	23.55	G300-C-BR	90.95	G300-C-SS	125.45	G300-C-ALSI	23.55
4"	G400-C-AL	36.75	G400-C-BR	132.00	G400-C-SS	173.95	G400-C-ALSI	36.75
5"	G500-C-AL ¹	103.00	G500-C-BR1	409.20				
6"	G600-C-AL	109.20			G600-C-SS	406.15		
8"	G800-C-AL1	335.00						



female coupler x hose shank

Does not interchange in the ½", 5", and 8" sizes with Dixon or Boss-Lock style cam and groove.

¹ Does not interchange in the ½" and 5" sizes with Dixon or Boss-Lock style cam and groove.

² supplied with stainless steel handles

 $^{^1}$ Does not interchange in the ½", 5", and 8" sizes with Dixon or Boss-Lock style cam and groove. 2 supplied with stainless steel handles