

Global Crimp Style Cam & Groove Type E Adapter x Hose Shank

Only use the crimp style shanks with the crimp style sleeves and ferrules.

Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon® products. Pressure rating is based on the seal of the mating part. See ratings on page D-5.



Hose ID	A380 Permanent Mold Aluminum		C38000 Forged Brass		316 Investment Cast Stainless Steel	
	Part #	Price/E	Part #	Price/E	Part #	Price/E
1"	G100-E-ALCR	\$7.55	G100-E-BRCR	\$23.00	G100-E-SSCR	\$28.40
1½"	G150-E-ALCR	11.45	G150-E-BRCR	37.60	G150-E-SSCR	44.95
2"	G200-E-ALCR	13.95	G200-E-BRCR	52.25	G200-E-SSCR	61.90
3"	G300-E-ALCR	23.45	G300-E-BRCR	108.35	G300-E-SSCR	117.95
4"	G400-E-ALCR	37.20	G400-E-BRCR	153.10	G400-E-SSCR	167.15
6"	G600-E-ALCR	105.00	---	---	G600-E-SSCR	472.00



A380 permanent mold aluminum



C38000 forged brass



316 investment cast stainless

Boss™ Ground Joint Stems

Only use the crimp style shanks with the crimp style sleeves and ferrules.

Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon® products. Pressure rating is based on the seal of the mating part. See ratings on page D-5.



Hose Shank x NPT	Plated Steel and / or Iron		Opt Qty
	Part #	Price/E	
2"	GB26	\$26.25	10
3"	GB36	90.00	5

- GB26 and GB36 has a machined shank to accept a Boss™ clamp, King Crimp™ sleeve or a ferrule



The King Crimp™ sleeve and ferrule are not intended for steam service.

