


## Gaskets

- check gasket color code to be certain it is recommended for the service intended
- use lubricant on gasket
- for services not listed contact Dixon for recommendations



### FKM

Size	Part #	Price/E
2"	<b>G200V</b>	<b>\$38.35</b>
3"	<b>G300V</b>	<b>57.05</b>
4"	<b>G400V</b>	<b>79.45</b>
6"	<b>G600V</b>	<b>110.95</b>
8"	<b>G800V</b>	<b>188.50</b>
10"	<b>G1000V</b>	<b>233.95</b>
12"	<b>G1200V</b>	<b>295.55</b>


#### Features:

- compound type: Fluoro Elastomer
- temperature range: **-13°F to 350°F**
- color code: black with blue stripe
- resistant to oxidizing acids, petroleum oils, hydraulic fluids, halogenated hydrocarbons and lubricants

### EPDM

Size	Part #	Price/E
1½"	<b>G150E</b>	<b>\$34.60</b>
2"	<b>G200E</b>	<b>9.25</b>
2½"	<b>G250E</b>	<b>11.10</b>
3"	<b>G300E</b>	<b>12.30</b>
4"	<b>G400E</b>	<b>17.90</b>
5"	<b>G500E</b>	<b>65.75</b>
6"	<b>G600E</b>	<b>32.30</b>
8"	<b>G800E</b>	<b>52.60</b>
10"	<b>G1000E</b>	<b>67.00</b>
12"	<b>G1200E</b>	<b>91.00</b>


#### Features:

- compound type: EPDM
- temperature range: **-22°F to 230°F**
- color code: black with green stripe
- for water, dilute acids, alkalies, salts, and many chemical services not involving hydrocarbons, oils, or gases.
- excellent oxidation resistance
- *Not for use with hydrocarbons* 

### Buna-N

Style	Black Buna with orange stripe		White Buna Gruvlok seal	
	Part #	Price/E	Part #	Price/E
1½"	<b>G150T</b>	<b>\$34.60</b>	---	---
2"	<b>G200T</b>	<b>9.25</b>	---	---
2½"	<b>G250T</b>	<b>11.10</b>	---	---
3"	<b>G300T</b>	<b>12.30</b>	---	---
4"	<b>G400T</b>	<b>17.90</b>	<b>G400N</b>	<b>\$36.50</b>
5"	<b>G500T</b>	<b>65.75</b>	---	---
6"	<b>G600T</b>	<b>32.30</b>	---	---
8"	<b>G800T</b>	<b>52.60</b>	---	---
10"	<b>G1000T</b>	<b>67.00</b>	---	---
12"	<b>G1200T</b>	<b>91.00</b>	---	---

#### Features:

- compound type: Buna-N
- temperature range: **-24°F to 176°F**
- for petroleum products, vegetable oils, mineral oils, and air contaminated with petroleum oils.
- *Not for use in hot water services* 

## Nuts and Bolts

Bolt Thread	Bolt Length	Torque Ft. Lbs.	Carbon Steel	
			Part #	Price/E
3/8"	2"	30	<b>BLT38200</b>	<b>\$5.95</b>
3/8"	2¼"	30	<b>BLT38225</b>	<b>19.30</b>
1/2"	2½"	50	<b>BLT50212</b>	<b>5.95</b>
1/2"	2¾"	50	<b>BLT50234</b>	<b>8.15</b>
1/2"	3"	50	<b>BLT50300</b>	<b>9.80</b>
5/8"	3¼"	75	<b>BLT58314</b>	<b>5.35</b>
3/4"	4¼"	75	<b>BLT75414</b>	<b>17.50</b>
7/8"	5"	200	<b>BLT78500</b>	<b>18.50</b>

#### Features:

- the nuts are a heavy hexagon design
- electroplated carbon steel
- The bolts are specifically designed for use with the couplings on pages 732-735.


#### Standards:

- conform to ASTM A183

R

## Groove Lube

#### Features:

- water soluble
- non-toxic
- non-corrosive
- non-flammable
- NSF approved for use with potable water
- *Should not be used with HDPE pipe.* 



Size	Container	Part #	Price/E
1 qt.	Tub	<b>GROOVLUB32</b>	<b>\$263.00</b>