

Features and Benefits



Power System Distribution Assemblies

- Available with up to 5 receptacles, wide variety of NEMA 5-20 receptacle grades
- Power pass thru option
- 16 gauge sheet metal enclosure ANSI 61 gray powder coat NEMA 1
- Device identification marking
- Versatile mounting provision
- Local or master switch
- LINKOSITY® connection



MSL3L1IGP

Note: Accepts PH2304 series cables.

Straight Blade - UL Type 1

Device Type	Switch Types	# Recepts	Receptacle Type	Receptacle Feature	Pass-thru	Custom Configurations*
M	SL = Switch Local	1	SG = Spec Grade HG = Hospital Grade CR = Corrosion Resistant	IG = Isolated Ground GF = Ground Fault SS = Surge Suppression 00 = Standard	P = Pass-thru** 0 = No Pass-thru	D = 2 Circuit A = A Phase B = B Phase C = C Phase
	SM = Switch Master	2				
	00 = No Switch	3				
		4				
		5				

Example: M SL 1 SG 00 P

Twist-Lock® - UL Type 1

Device Type	Switch Types	# Recepts	Receptacle Type	Receptacle Feature	Pass-thru	Custom Configurations*
M	SL = Switch Local	1	L1 = 15A L2 = 20A	IG = Isolated Ground 00 = Standard	P = Pass-thru 0 = No Pass-thru	6 = 250V
	SM = Switch Master	2				
	00 = No Switch	3				
		4				
		5				

Example: M 00 3 L1 IG 0

Note: Local switches control all receptacles in a box. Master switches control local and downstream receptacles. Consult factory for alternate wiring schemes.

*Consult factory for wiring specifications and connecting cables.

**Pass-thru on phase tap boxes are 3Ø.

Switch Only (ON/OFF) - UL Type 1

Device Type	Switch Types	Switch Style	Poles
S	1 = 1 Gang	2W = ON/OFF	1P = Single Pole DP = Two Pole
	2 = 2 Gang		
	3 = 3 Gang		

Example: S 1 2W 1P

Switch Only (4-Way) - UL Type 1

Device Type	Switch Types	Switch Style
S	1 = 1 Gang	4W = 4 Way

Example: S 1 4W

Switch Only (3-Way) - UL Type 1

Device Type	Switch Types	Switch Style	Position
S	1 = 1 Gang	3W = 3 Way	M = Main
			R = Remote LM = Line to Main LR = Load to Remote

Example: S 1 3W M

Note: For use with Px2304PBxxx series cables.

Features

Receptacle Types		CR	HG	SG	L1
00	Standard	HBL53CM62	HBL8300GY	5362G	HBL4700
IG	Isolated Ground	—	—	CR5352IGGY	IG4700A
GF	Ground Fault	—	GFRST83GY	GF20GYLA	—
SS	Surge Suppression	—	HBL8362GYSA	HBL5362GYSA	—
Switch Types		CR	HG	SG	L1
SL	Local ON/OFF	—	—	HBL1221PL	—
SM	Master ON/OFF	—	—	HBL1221PL	—