

Hubbell Wall Duct Fittings

Ordering Information Notes:

1. Common use sizes are listed below.Contact factory for other configurations or see page S-6 for Range of Offering table.

2. Wall Duct part numbers are for reference only. All Wall Duct orders are lot billed with a generic TW prefix project specific part numbers. Please contact your local Hubbell Territory Manager for all Hubbell Duct quotations.

	Description	Overall Depth	Body Width	Cover Width	Flush Catalog Number	Cover Width	Surface Catalog Number	
External Elbows	Internal / External Elbow Transitions from surface wall duct to surface style ceiling duct. Flush wall duct to surface style ceiling duct available	3½" 3½" 3½"	9 ¹³ ⁄16" 11 ¹³ ⁄16" 17 ¹³ ⁄16"	12" 14" 20"	 	10" 12" 18"	SPOWI/D10S SPOWI/D12S SPOWI/D18S	
sterne	upon request. Provided with two cover plates, one coupling and necessary screws.							
/ E	Internal / External Elbow, Sweep	31⁄2"	9 ¹³ ⁄16"	12"	_	10"	SPOWSWI/D10S	
a	Transitions from surface wall duct to	31⁄2"	11 ¹³ ⁄16"	14"	-	12"	SPOWSWI/D12S	
Internal /	surface style ceiling duct. Flush wall duct to surface style ceiling duct available upon request. Provided with two cover plates, one coupling and necessary screws.	31⁄2"	17 ¹³ ⁄16"	20"	-	18"	SPOWSWI/D18S	
	Vertical "T" Unit	31⁄2"	9 ¹³ ⁄16"	12"	OWVT/D10F	10"	OWVT/D10S	
	Forms a 90° Vertical "T". Provided with	31⁄2"	11 ¹³ ⁄16"	14"	OWVT/D12F	12"	OWVT/D12S	
	three cover plates, two couplings and necessary screws.	3½"	17 ¹³ ⁄16"	20"	OWVT/D18F	18"	OWVT/D18S	
Units								*
"L	Horizontal "T" Unit	31⁄2"	9 ¹³ ⁄16"	12"	OWT/D10F	10"	OWT/D10S	
5	Forms a 90° Horizontal "T". Provided	31⁄2"	11 ¹³ ⁄16"	14"	OWT/D12F	12"	OWT/D12S	
	with one cover plate, one coupling and necessary screws. Tunnels are ordered separately.	3½"	17 ¹³ ⁄16"	20"	OWT/D18F	18"	OWT/D18S	
	"X" Unit	31⁄2"	9 ¹³ ⁄16"	12"	OWX/D10F	10"	OWX/D10S	
	Forms intersection of four perpendicular	31/2"	1 1 ¹³ ⁄16"	14"	OWX/D12F	12"	OWX/D12S	
"X" Unit	ducts. Provided with one cover plate, two coupling and necessary screws. Tunnels are ordered separately.	31⁄2"	17 ¹³ ⁄16"	20"	OWX/D18F	18"	OWX/D18S	

Vertical Riser Fittings	Description	For Trench Width	For Wall Duct (Width x Depth)	Flush Catalog Number	Surface Catalog Number	
	Vertical Riser Fitting, Straight Transitions from trench duct to a vertical run of wall duct. Mounts on trench in place of cover. Removable front cover. Standard height above finish floor – 12" (7" for OWR/ D12x10). Standard depth – 3½". Provided with one coupling and necessary screws.	10" 12" 18" 12"	10" x 3½" 12" x 3½" 18" x 3½" 10" x 3½"	OWR/D10F OWR/D12F OWR/D18F OWR/D12-10F	OWR/D10S OWR/D12S OWR/D18S OWR/D12-10S	
	Vertical Riser Fitting, Sweep Transitions from trench duct to a vertical run of wall duct. Mounts on trench in place of cover. Removable front cover. Standard height above finish floor — 12". Standard depth — 3½". Provided with one coupling and necessary screws.	10" 12" 18" 12"	10" x 3½" 12" x 3½" 18" x 3½" 10" x 3½"	OWSWR/D10F OWSWR/D12F OWSWR/D18F OWSWR/D12-10F	OWSWR/D10S OWSWR/D12S OWSWR/D18S OWSWR/D12-10S	

ng	Description	Overall Depth	Flush Wall Duct Body Width	Surface Cover Width	Catalog Number	
pter Fitti	Flush to Surface Adapter	31⁄2"	9 ¹³ ⁄16"	10"	OWB/D10-10	
	Transitions from flush wall duct to	31⁄2"	1 1 ¹³ ⁄16"	18"	OWB/D12-18	
	perpendicular surface wall duct. Provided	31⁄2"	17 ¹³ ⁄16"	12"	OWB/D18-12	
	with one cover plate, two couplings and	31⁄2"	17 ¹³ ⁄16"	18"	OWB/D18-18	
da	necessary screws.					
◄						