

Compound Gauges

Features:

- ASME B40.1, Grade B accuracy ($\pm 3-2-3$ % accuracy)
- ABS plastic case
- bronze bourdon tube / brass socket
- polycarbonate crystal
- black aluminum pointer
- brass movement with polyester segment, designed for extended wear
- temperature range of -40°F to 150°F



GL310

2 1/2" face - 1/4" center back mount

Mercury (Hg)	PSI Range	Fig. Inter. (Hg / PSI)	Min.Grad. (Hg / PSI)	Part #	Price/E
30"	0-160	30 / 20	5 / 5	GC210	\$29.25

2 1/2" face - 1/4" lower mount

Mercury (Hg)	PSI Range	Fig. Inter. (Hg / PSI)	Min.Grad. (Hg / PSI)	Part #	Price/E
30"	0-100	30 / 10	5 / 2	GL310	\$20.40
30"	0-160	30 / 20	10 / 10	GL110	20.40
30"	0-200	30 / 20	10 / 10	GL315	20.40

Vacuum Gauges

Features:

- ASME B40.1, Grade B accuracy ($\pm 3-2-3$ % accuracy)
- ABS plastic case
- bronze bourdon tube
- polycarbonate crystal
- black aluminum pointer
- brass movement with polyester segment, designed for extended wear
- temperature range: -40°F to 150°F



GL105

2" face - 1/4" lower mount

Mercury (Hg)	Fig. Inter. (Hg / PSI)	Min.Grad. (Hg / PSI)	Part #	Price/E
30"	5"	.5"	GL105	\$19.20

2" face - 1/4" center back mount

Mercury (Hg)	Fig. Inter. (Hg / PSI)	Min.Grad. (Hg / PSI)	Part #	Price/E
30"	5"	.5"	GC205	\$22.20

2 1/2" face - 1/4" lower mount

Mercury (Hg)	Fig. Inter. (Hg / PSI)	Min.Grad. (Hg / PSI)	Part #	Price/E
30"	5"	.5"	GL305	\$20.40

Brass Welding Gauges

Features:

- 3-2-3% accuracy according to ASME B40.100 Grade B
- polished drawn brass case
- twist-lock polycarbonate window
- copper alloy bourdon tube
- "Use no oil" written in red on face
- temperature range: -40°F to 140°F



GBRW4000

2 1/2" face - 1/4" lower mount

PSI Range	Fig. Inter. (Hg / PSI)	Min.Grad. (Hg / PSI)	Part #	Price/E
0-30	5	.5	GBRW30	\$61.50
0-30	5	.5	GBRW30R¹	61.50
0-60	10	1	GBRW60	61.50
0-100	20	2	GBRW100	61.50
0-200	50	5	GBRW200	61.50
0-400	100	10	GBRW400	61.50
0-600	100	10	GBRW600	61.50
0-4000	500	100	GBRW4000	64.75

¹ red band between 15 to 30 PSI on GBRW30R