

ABS Standard Dry Gauges

Features:

- ASME B40.1, Grade B ($\pm 3-2-3\%$ accuracy)
- PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.
- ABS plastic case
- c-shaped bronze safety bourdon tube (600 PSI and lower)
- helical wound bronze safety bourdon tube (1000 PSI and higher)
- polycarbonate crystal
- black aluminum pointer
- temperature range: **-40°F to 150°F**

Center Back Mount

1½" face ⅛" center back mount

PSI Range	Fig. Inter.	Minor Grad.	Part #	Price/E
0-30	5	.5	GC605	\$16.70
0-60	5	1	GC610	16.70
0-100	10	2	GC615	16.70
0-160	20	5	GC620	16.70
0-200	20	5	GC625	16.70

2" face ¼" center back mount

PSI Range	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	1	.5	GC200	\$22.20
0-30	5	.5	GC215	20.70
0-60	5	1	GC220	20.70
0-100	10	2	GC225	20.70
0-160	20	5	GC230	20.70
0-200	20	5	GC235	20.70
0-300	30	5	GC240	20.70



GC230

Lower Mount

2" face ¼" lower mount

PSI Range	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	1	.5	GL100	\$19.20
0-30	5	.5	GL115	17.75
0-60	5	1	GL120	17.75
0-100	10	2	GL125	17.75
0-160	20	5	GL130	17.75
0-200	20	5	GL135	17.75
0-300	30	5	GL140	17.75

2½" face ¼" lower mount

PSI Range	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	1	.5	GL300	\$20.40
0-30	5	.5	GL320	18.95
0-60	5	1	GL325	18.95
0-100	10	2	GL330	18.95
0-160	20	5	GL335	18.95
0-200	20	5	GL340	18.95
0-300	30	5	GL345	18.95
0-400	50	10	GL347	18.95
0-600	50	10	GL350	18.95
0-1000	200	20	GL355	28.10
0-1500	300	50	GL360	28.10
0-2000	400	50	GL365	28.10
0-3000	500	100	GL370	28.10
0-5000	1000	100	GL375	28.10



GL140

3½" face ¼" lower mount

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	1	.5	GS15-4	\$28.10
0-30	5	.5	GS30-4	26.60
0-60	5	1	GS60-4	26.60
0-100	10	2	GS100-4	26.60
0-160	20	5	GS160-4	26.60
0-200	20	5	GS200-4	26.60
0-300	30	5	GS300-4	26.60
0-400	50	10	GS400-4	26.60
0-600	50	10	GS600-4	26.60
0-1000	200	20	GS1000-4	36.95