


## Boss Holedall Fittings

### Applications:

- designed for air and liquid applications where a permanent, low profile clamping system is desired
- not for steam service 

### Features:

- supplied with carbon steel ferrules
- consult Dixon for swage and/or crimp specifications

| Size | Hose OD  |          | Plated Iron / Steel |                | Stainless Steel |                 |
|------|----------|----------|---------------------|----------------|-----------------|-----------------|
|      | From:    | To:      | Part #              | Price/E        | Part #          | Price/E         |
| ¾"   | 1-10/64" | 1-14/64" | <b>GF26P1</b>       | <b>\$58.15</b> | ---             | ---             |
|      | 1-15/64" | 1-18/64" | <b>GF26P2</b>       | <b>58.15</b>   | ---             | ---             |
|      | 1-19/64" | 1-22/64" | <b>GF26P3</b>       | <b>58.15</b>   | ---             | ---             |
| 1"   | 1-30/64" | 1-34/64" | <b>GF36P1</b>       | <b>61.55</b>   | ---             | ---             |
|      | 1-35/64" | 1-38/64" | <b>GF36P2</b>       | <b>61.55</b>   | ---             | ---             |
|      | 1-39/64" | 1-42/64" | <b>GF36P3</b>       | <b>61.55</b>   | ---             | ---             |
| 1½"  | 1-20/64" | 2"       | <b>GF61P1</b>       | <b>125.35</b>  | <b>RGF61P1</b>  | <b>\$440.00</b> |
|      | 2-1/64"  | 2-8/64"  | <b>GF61P2</b>       | <b>125.35</b>  | <b>RGF61P2</b>  | <b>440.00</b>   |
|      | 2-9/64"  | 2-16/64" | <b>GF61P3</b>       | <b>125.35</b>  | ---             | ---             |
| 2"   | 2-36/64" | 2-40/64" | <b>GF81P1</b>       | <b>128.75</b>  | <b>RGF81P1</b>  | <b>580.00</b>   |
|      | 2-41/64" | 2-48/64" | <b>GF81P2</b>       | <b>128.75</b>  | <b>RGF81P2</b>  | <b>580.00</b>   |
|      | 2-49/64" | 2-56/64" | <b>GF81P3</b>       | <b>128.75</b>  | ---             | ---             |
| 3"   | 3-26/64" | 3-40/64" | <b>GF111P1</b>      | <b>355.00</b>  | ---             | ---             |
|      | 3-41/64" | 3-48/64" | <b>GF111P2</b>      | <b>355.00</b>  | ---             | ---             |
|      | 3-49/64" | 3-56/64" | <b>GF111P3</b>      | <b>355.00</b>  | ---             | ---             |



E

## Boss Adapters

### Features:

- plated steel and / or iron
- designed to fit the standard ground joint spuds on page 106
- supplied with a wing nut, as shown
- for safety tags and safety tape, see page 778

#### male NPT adapters

| Size | Part #                     | Price/E        | Pkg Qty |
|------|----------------------------|----------------|---------|
| ¾"   | <b>GMAS6</b>               | <b>\$51.50</b> | 25      |
| 1"   | <b>GMAS11</b>              | <b>53.70</b>   | 25      |
| 1¼"  | <b>GMAS16</b>              | <b>74.00</b>   | 10      |
| 1½"  | <b>GMAS21</b>              | <b>88.85</b>   | 10      |
| 2"   | <b>GMAS26</b> <sup>1</sup> | <b>92.50</b>   | 10      |

<sup>1</sup> uses a special wing nut, part # B27-3

#### female NPT adapters

| Size | Part #                     | Price/E         |
|------|----------------------------|-----------------|
| ¾"   | <b>GFAS6</b>               | <b>\$101.40</b> |
| 1"   | <b>GFAS11</b>              | <b>110.00</b>   |
| 1¼"  | <b>GFAS16</b>              | <b>125.00</b>   |
| 1½"  | <b>GFAS21</b> <sup>1</sup> | <b>150.00</b>   |
| 2"   | <b>GFAS26</b>              | <b>162.00</b>   |


<sup>1</sup> part is produced as a welded fabrication



## Boss Wing Nut Caps

### Features:

- plated steel and / or iron
- supplied with 12" chain and washer
- for best results, use with washer style spuds and washers on pages 108 and 109

 Boss wing nut caps are not intended for pressure applications.

| Size        | Part #       | Price/E        | Opt Qty |
|-------------|--------------|----------------|---------|
| ¾" and 1"   | <b>B12SC</b> | <b>\$44.60</b> | 25      |
| 1¼" and 1½" | <b>B17SC</b> | <b>55.30</b>   | 25      |
| 2"          | <b>B27SC</b> | <b>82.25</b>   | 10      |
| 3"          | <b>B37SC</b> | <b>131.25</b>  | 5       |

