Grease Whip Hose Assemblies

- for use with hand grease guns only
- one piece brass crimp couplings
- 1/8"-27 male NPT thread, solid base
- US manufactured 3/16" I.D. hose exceeds SAE 100R1-AT
- Strain relief spring option is available as a special, consult Dixon for pricing.
 - working pressure: 3000 PSI



Part #	Assembly Length	Retail Pack	Price/E
GWH-0800	8"	n/a	\$11.87
GWH-1200	12"	Add "R" suffix to part number	14.25
GWH-1800	18"	Add "R" suffix to part number	17.91
GWH-2400	24"	n/a	21.55
GWH-3600	36"	n/a	28.80
GWH-4800	48"	n/a	36.09
GWH-6000	60"	n/a	43.27

Grease Whip Hose Fittings Features:

male and female fittings are designed to be crimped on

grease hose couplers



Zinc Plated Steel Part #	Description	Price/E	Pkg Qty
GWH-C	grease hose coupler	\$8.15	25
GWHC-FF	full flow grease hose coupler	8.15	25

male NPT thread - chamfered base



<i>Brass</i> Part #	Description	Price/E	Pkg Qty
001-0055	1/8"-27 male NPT thread, drilled and chamfered base	\$2.93	100

male NPT thread - solid base



Brass Part #	Description		Pkg Qty
001-0260	1/6"-27 male NPT thread, solid base	\$2.69	100

female NPT thread



<i>Brass</i> Part #	Description	Price/E	Pkg Qty
001-0860	1/8"-27 female NPT thread	\$5.20	100

Grease Whip Fittings



Zinc Plated Steel Part #	Threads	Description	Overall Length	Thread Length	Hex	Price/E	Pkg Qty
GWHZ000	1/8-27 NPT	straight	.660	.260	.430	\$0.81	100
GWHZ045	1/8-27 NPT	45°	.860	.280	.430	1.11	100
GWHZ090	1/8-27 NPT	90°	.830	.310	.430	1.12	100
GWHZ400	1/4-28 tapered SAE-LT	straight	.530	.200	.312	0.63	100
GWHZ445	1/4-28 tapered SAE-LT	45°	.800	.200	.375	1.13	100
GWHZ490	1/4-28 tapered SAE-LT	90°	1.20	.200	.375	1.13	100