400# Nitrile Covered Fire Hose - Light Duty Red

Application:

ideal for industrial and construction washdown and discharge applications

Features:

- synthetic rubber compound formulated for flexibility and abrasion and chemical resistance
- ribbed for hose protection and easy handling
- · outer construction: thin ribbed nitrile
- · tube construction: nitrile
- proof pressure: 400 PSI at ambient temperature (70°F)
- service test pressure: 200 PSI at ambient temperature (70°F)
- working pressure: 180 PSI at ambient temperature (70°F)

Uncoupled

Size	Bowl	Length	Part #	Price/E
2"	21/4"	50'	H420R50UC	\$545.30



Coupled with Female and Male NPSH thread, brass expansion ring couplings with rocker lugs

Size	Length	Part #	Price/E
2"	50'	H420R50RBS	\$753.85



other lengths, threads and couplings



500# Nitrile Covered Fire Hose - Light Duty Red

Application:

ideal for industrial and construction washdown and discharge applications

Features:

- · outer construction: thin ribbed nitrile
- · tube construction: nitrile
- proof pressure: 500 PSI at ambient temperature (70°F)
- service test pressure: 250 PSI at ambient temperature (70°F)
- working pressure: 225 PSI at ambient temperature (70°F)
- Consult Dixon for pricing and availability of 25' lengths, other colors, threads and configurations

Uncoupled

Size	Bowl	Length	Part #	Price/E
1½"	1-13/16"	50'	H515R50UC	\$390.60
21/2"	2-13/16"	50'	H525R50UC	573.60
1½"	1-13/16"	100'	H515R100UC	781.20
21/2"	2-13/16"	100'	H525R100UC	1147.20



P

Coupled with female and male expansion ring couplings

Size	Length	Part #	Rocker Lug Aluminum NST (NH) RAF	Rocker Lug Brass NST (NH) RBF	Pin Lug Brass NST (NH) PBF	Rocker Lug Aluminum NPSH RAS
1½"	50'	H515R50	\$488.95	\$510.75	\$565.50	\$488.95
21/2	50'	H525R50	726.50	876.70	920.00	726.50
1½"	100'	H515R100	896.00			896.00
21/2"	100'	H525R100	1065.05			1064.95



Consult Dixon for pricing and availability for any of the following options:

- other lengths, threads and couplings
- other colors: yellow, red, blue and black