



## Construction Site Lighting

Hubbell's outdoor approved construction site lighting line includes both heavy duty metal halide lights and light strings for working in rugged environments. The metal halide fixtures feature extremely strong and compact heads with bulbs rated to last 10,000 hours. All frames are powder-coated yellow for safety and are constructed of a durable 1.25 inch, 12 gauge steel tube.

We have light strings for all applications in a variety of models as well as a choice of metal or plastic guards. Light sockets are spaced 10 feet apart and all sockets, plugs, and connectors are molded for added durability. In addition, the highly impact-resistant material makes for easy transportation and storage when not in use. Bulbs can be incandescent, fluorescent or LED. Consider choosing LED lighting for a durable bulb that saves energy, provides instant illumination and are rated to last 50,000 hours.



HBLMH1000



HBLMH400



HBLLEDHB120



HBL182S50LEDH



HBL143SJ100PS



HBLFS2549  
Straps not Shown

## Metal Halide and LED Lights

Description	Rating	Watts	Lumen Output	Cord Length	Catalog Number
5 -10 ft. metal halide cart light with portable detachable ballast.	15A 125V	1,000	110,000	—	<b>HBLMH1000</b>
6 -12 ft. metal halide cart light.	15A 125V	2,000	220,000	—	<b>HBLMH2000</b>
High bay metal halide light with wire guard.	15A 125V	400	29,000	3 ft.	<b>HBLMH400</b>
High bay LED light with wire guard.	15A 125V	120	14,000	5 ft.	<b>HBLLEDHB120</b>

## LED Stringer Lights

Description	No. of Fixtures	Rating	Cord Type	Lumen Output	Cord Length	Catalog Number
90 LEDs per fixture, light string with magnetic base included.	1	15A 125V	#18/2 SJTW	450*	20 ft.	<b>HBL182S20LED</b>
90 LEDs per fixture, light string.	5	15A 125V	#18/2 SJTW	450*	50 ft.	<b>HBL182S50LED</b>
	10	15A 125V	#18/2 SJTW	450*	100 ft.	<b>HBL182S100LED</b>
60 LEDs per fixture, light string with magnetic base included.	1	15A 125V	#18/2 SJTW	1,100*	20 ft.	<b>HBL182S20LEDH</b>
	5	15A 125V	#18/2 SJTW	1,100*	50 ft.	<b>HBL182S50LEDH</b>
28W High power LED light string with inline ON/OFF switch.	—	15A 125V	#16 AWG SJTOW	2,928	6 ft.	<b>HBLLS2834</b>
Magnetic clip bracket for LED.	—	—	—	—	—	<b>HBLSTMC</b>

Note: \*Lumens per fixture.

## A Type (Edison) Twist-Lock® and Straight Blade Light Strings

Description	Max Watts**	Rating	Cord Type	Fixtures	Cord Length	Catalog Number
Twist-Lock® light string; plastic guards.	150	20A 125V	#12/3 STW	10	100 ft.	<b>HBL123S100PT</b>
	150	20A 125V	#12/3 STJW	10	100 ft.	<b>HBL123SJ100PT</b>
Twist-Lock® light string; metal guards.	150	20A 125V	#12/3 STW	10	100 ft.	<b>HBL123S100MT</b>
Straight Blade light string; plastic guards.	150	15A 125V	#14/2 STJW	10	100 ft.	<b>HBL142SJ100PS</b>
	150	15A 125V	#14/3 STJW	10	100 ft.	<b>HBL143SJ100PS</b>
	150	15A 125V	#12/3 STW	10	100 ft.	<b>HBL123S100PS</b>
	150	15A 125V	#12/3 STJW	10	100 ft.	<b>HBL123SJ100PS</b>
Straight Blade light string; metal guards.	150	15A 125V	#12/3 STW	10	100 ft.	<b>HBL123S100MS</b>
Straight Blade light string; plastic guards.	150	15A 125V	#12/3 STW	5	50 ft.	<b>HBL123S50PS</b>
Straight Blade light string; metal guards.	150	15A 125V	#12/3 STW	5	50 ft.	<b>HBL123S50MS</b>
Replacement plastic guard for temporary light strings.	—	—	—	—	—	<b>HBLSTPG</b>
Replacement heavy duty metal guard for temporary light strings.	—	—	—	—	—	<b>HBLSTMG</b>

Note: \*\*Max watts per fixture. **HBL143SJ100PS** light strings are rated for 1875 Watts total. The total wattage must be considered when daisy chaining lights strings to each other.

## Fluorescent Light Strings

Description	Wattage	Rating	Cord Type	Lumen Output	Cord Length	Catalog Number
Fluorescent light string, 34.5" single fixture with hanging straps	50	15A 125V	#16 AWG SJTOW	3,750	6 ft.	<b>HBLFS5035</b>
Fluorescent light string, 48.5" single fixture with hanging straps	25	15A 125V	#16 AWG SJTOW	2,125	6 ft.	<b>HBLFS2549</b>