

30 Amp, 125, 250 Volts and 277 Volts AC 2 Pole, 3 Wire, Grounding



30A 125V NEMA L5-30P 2 HP	30A 250V NEMA L6-30P 2 HP	30A 277V AC NEMA L7-30P 3 HP
---------------------------------	---------------------------------	------------------------------------

Connector Bodies

Watertight Safety-Shroud®		IP66 SUITABILITY	UL Type 4x, 12
Description	Cord Dia.	Catalog Number	
Black Valox® housing, white Valox® clamps.	.360"-.930" (9-24)	HBL2613SW	HBL2623SW -
Reverse service, black Valox® housing, white Valox® clamps (use with HBL2615SWR), (Not shown).	.360"-.930" (9-24)	HBL2613SR	- -




HBL2613SW

Insulgrip®		IP20 SUITABILITY	
Description	Cord Dia.	Catalog Number	
Black and white nylon.	.360"-.930" (9-24)	HBL2613	HBL2623 HBL2633
Heat stabilized, gray nylon, 220° F (104° C).	.360"-.930" (9-24)	HBL2613F	HBL2623F -
Corrosion resistant, yellow nylon.	.360"-.930" (9-24)	HBL26CM13	HBL26CM23 -
All black nylon.	.360"-.930" (9-24)	HBL2613BK	HBL2623BK -



HBL2623



HBL2613VY

Note: See page B-52 for accessories.

Valise®		IP20 SUITABILITY	
Description	Cord Dia.	Catalog Number	
Yellow nylon.	.590"-.930" (15.0-23.6)	HBL2613VY	HBL2623VY -
Corrosion resistant, yellow nylon.	.590"-.930" (15.0-23.6)	HBL26CM13V	- -
Black nylon.	.590"-.930" (15.0-23.6)	HBL2613VBK	HBL2623VBK -



HBL2610SW

Note: See page B-53 for accessories.

Receptacles

Watertight Safety-Shroud®		IP66 SUITABILITY	UL Type 4x, 12
Description	Cord Dia.	Catalog Number	
Gray Valox® housing and flange, back wired.	.590"-.930" (15.0-23.6)	HBL2610SW	HBL2620SW -

Note: See page B-54 for accessories.

Safety-Shroud® Twist-Lock®		IP20 SUITABILITY	
Description	Cord Dia.	Catalog Number	
Gray Valox® angle housing, one gang, back wired.	.590"-.930" (15.0-23.6)	HBL2610AR	HBL2620AR -
Gray Valox® surface mounting, one gang, back wired.	.590"-.930" (15.0-23.6)	HBL2610SR	HBL2620SR -
Gray Valox® semi-flush, two gang, back wired.	.590"-.930" (15.0-23.6)	HBL2610SR2	HBL2620SR2 -



HBL2620AR


Single Flush Receptacles		IP20 SUITABILITY	
Description	Cord Dia.	Catalog Number	
Black nylon face, back and side wired.	.590"-.930" (15.0-23.6)	HBL2610	HBL2620 HBL2630
Blue nylon face, back and side wired.	.590"-.930" (15.0-23.6)	HBL2610M6	HBL2620M6 -
Isolated ground, orange nylon face, back and side wired.	.590"-.930" (15.0-23.6)	IG2610	IG2620 -
Corrosion resistant, yellow nylon face, back and side wired.	.590"-.930" (15.0-23.6)	HBL26CM10	HBL26CM20 -
Ring terminal connection.	.590"-.930" (15.0-23.6)	HBL2610RT	HBL2620RT -

Note: See page B-52 for accessories.

Insulgrip® Flanged Receptacles

Description	Cord Dia.	Catalog Number	
Nylon casing, back wired.	.590"-.930" (15.0-23.6)	HBL2616	HBL2626 HBL2636
Heat stabilized, gray nylon, 220° F (104° C).	.590"-.930" (15.0-23.6)	HBL2616F	HBL2626F -

Note: See page B-52 for accessories.



HBL2620SR

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

Dimensions in Inches (mm)