

## FloMAX 3/4" Series

**Features:**

- 6 nozzle and receiver sets color coded for quick identification of mating parts; each color nozzle and receiver only couples with matching color component providing complete protection against cross contamination
- maximum flow rate: 45 GPM at 70 PSI
- working pressure rating: **200 PSI**

D



**Nozzles**

Male Thread	Description	Anodized Aluminum	
		Part #	Price/E
3/4" NPT	red nozzle with plug	<b>ENBL-P</b>	<b>\$610.95</b>
	gold nozzle with plug	<b>ENBL-P2</b>	<b>610.95</b>
	teal nozzle with plug	<b>ENBL-P3</b>	<b>610.95</b>
	violet nozzle with plug	<b>ENBL-P4</b>	<b>610.95</b>
	navy nozzle with plug	<b>ENBL-P5</b>	<b>610.95</b>
	copper nozzle with plug	<b>ENBL-P6</b>	<b>610.95</b>

**Receivers**

Male Thread	Description	Anodized Aluminum	
		Part #	Price/E
3/4" NPT	red receiver with cap	<b>ERS-C</b>	<b>\$296.75</b>
	gold receiver with cap	<b>ERS-C2</b>	<b>296.75</b>
	teal receiver with cap	<b>ERS-C3</b>	<b>296.75</b>
	violet receiver with cap	<b>ERS-C4</b>	<b>296.75</b>
	navy receiver with cap	<b>ERS-C5</b>	<b>296.75</b>
	copper receiver with cap	<b>ERS-C6</b>	<b>296.75</b>



- ERS series is available with JIC bulkhead base, substitute 'J' for 'S', example: ERJ-C2

## FloMAX High Flow 1" Series

**Features:**

- 7 nozzle and receiver sets color coded for quick identification of mating parts; each color nozzle and receiver only couples with matching color component provides complete protection against cross contamination
- nozzle/receiver combination has a flow area equivalent to a 1" schedule 80 pipe
- working pressure: **500 PSI** with burst pressure: **1500 PSI**
- all wear parts are stainless steel providing long life and corrosion resistance
- all non-wear parts are colored anodized aircraft grade aluminum providing high strength, lightweight and corrosion resistance
- standard nozzle mounting is a 1" female NPT and for the receiver a 1" male NPT; receivers supplied with 1" female NPT threaded base
- nozzle incorporates a "ball lock" mechanism ensuring smooth and reliable operation
- nozzle length: 3.90" (99 mm)
- receiver length: 3.44" (87 mm)
- nozzle and receiver coupled length: 5.44" (138 mm)
- diameter: 2.50" (64 mm)
- hex size: 2" (51 mm)

**Nozzles**

Female NPT	Description	Anodized Aluminum	
		Part #	Price/E
1"	red nozzle with plug	<b>HFN-P1</b>	<b>\$685.10</b>
	gold nozzle with plug	<b>HFN-P2</b>	<b>685.10</b>
	teal nozzle with plug	<b>HFN-P3</b>	<b>685.10</b>
	violet nozzle with plug	<b>HFN-P4</b>	<b>685.10</b>
	navy nozzle with plug	<b>HFN-P5</b>	<b>685.10</b>
	copper nozzle with plug	<b>HFN-P6</b>	<b>685.10</b>
	blue/gray nozzle with plug	<b>HFN-P7</b>	<b>685.10</b>

**Receivers**

Male NPT	Description	Anodized Aluminum	
		Part #	Price/E
1"	red receiver with cap	<b>HFR-C1</b>	<b>\$432.00</b>
	gold receiver with cap	<b>HFR-C2</b>	<b>432.00</b>
	teal receiver with cap	<b>HFR-C3</b>	<b>432.00</b>
	violet receiver with cap	<b>HFR-C4</b>	<b>432.00</b>
	navy receiver with cap	<b>HFR-C5</b>	<b>432.00</b>
	copper receiver with cap	<b>HFR-C6</b>	<b>432.00</b>
	blue/gray receiver with cap	<b>HFR-C7</b>	<b>432.00</b>

