

Single Hydrant Gate Valves with Hand Wheel

**Application:**

- used to throttle the flow from a fire hydrant preventing damage to the hydrant

Features:

- O-ring seal
- U/L listed
- for use on standpipes and fire pumps where U/L listing is required
- maximum operating pressure: **175 PSI** (water only) at 70°F (21°C)

Inlet Female	Outlet Male	Cast Red Brass Part #	Price	Wt. Lbs.
2½" NST (NH)	2½" NST (NH)	UHGV250F	\$450.00	9.0
2½" NST (NH)	2½" NST (NH)	UHGV250F-D	521.00	9.0
2½" CT	2½" CT	UHGV250 ¹	POR	9.0

¹ Customer Thread (*must specify*) refer to legend on page 566

**Replacement Part**

Description	Part #	Price	Wt. Lbs.
handwheel	UHGV250-W	\$23.00	.25

Single Hydrant Gate Valves with Speed Handle

05-116

Application:

- used to throttle the flow from a fire hydrant preventing damage to the hydrant

Features:

- pin lug swivel, non-rising stem, aluminum speed handle
- rubber seal
- for use on hydrants, standpipes, and fire pumps
- maximum operating pressure: **175 PSI** (water only) at 70°F (21°C)

Inlet Female	Outlet Male	Cast Brass Part #	Price	Wt. Lbs.
2½" NST (NH)	2½" NST (NH)	HGV250F	\$409.10	8.8
2½" NST (NH)	2½" NST (NH)	HGV250F-D	POR	8.8
2½" NST (NH)	2½" NPSH	HGV250	419.35	8.6
2½" CT	2½" CT	HGV250 ¹	POR	8.6

¹ Customer Thread (*must specify*) refer to legend on page 566



P

Replacement Part

Description	Aluminum Part #	Price	Wt. Lbs.
speed handle	HGV250-H	\$18.00	.20