# Features:

- used on manifold and line connections, pump, suction and mud service
- up to 4,000 PSI NSCWP (non-shock cold working pressure
- red sub, black nut

Size	Configuration	NSCWP (PSI)	Forged Steel Part #	Price/E
2"	threaded	4000	HU400200	\$148.00
3"	threaded	4000	HU400300	305.25
4"	threaded	4000	HU400400	387.45



# **602 Series**

#### Features:

- for use in mud, manifold service and truck mounting applications running air, water, oil, gas or mud up to 6,000 PSI NSCWP (non-shock cold working pressure)
- lip type seal ring minimizes fluid flow turbulence while creating a pressure seal
- orange sub. black nut

Size	Configuration	NSCWP Forged Steel		
Size	Configuration	(PSI)	Part #	Price/E
1"	threaded	6000	HU602100	\$116.00
2"	threaded	6000	HU602200	269.20
2"	buttweld	6000	HU602200BW NE	234.85
3"	threaded	6000	HU602300	<b>375.00</b>
3"	buttweld	6000	HU602300BW NEV	446.15
4"	threaded	6000	HU602400	550.00
4"	buttweld	6000	HU602400BW NEW	704.50
			TATE A	



### Features:

# 1002 Series

- for use in high pressure systems and truck mounting applications running air, water, oil, gas
  or mud up to 10,000 PSI NSCWP (non-shock cold working pressure)
- lip type seal ring minimizes fluid flow turbulence while creating a pressure seal
- blue sub, red nut

Size	Configuration	NSCWP	Forged Steel	
OIZC	Comiguration	(PSI)	Part #	Price/E
1"	threaded	10000	HU1002100	\$223.15
2"	threaded	10000	HU1002200	293.40
2"	buttweld	10000	HU1002200BW <b>№</b>	270.00
3"	threaded	10000	HU1002300	450.00
3"	buttweld	10000	HU1002300BW NE	610.55
4"	threaded	10000	HU1002400	758.20
4"	buttweld	10000	HU1002400BW NE	751.45



### Features:

# 1502 Series

- for use in extreme high pressure applications running air, water, oil, gas or mud up to 15,000 PSI NSCWP (non-shock cold working pressure)
- lip type seal ring minimizes fluid flow turbulence while creating a pressure seal
- red sub, blue nut

Size	Configuration	NSCWP	Forged Steel	
3126	Configuration	(PSI)	Part # Price/	/E
2"	threaded	15000	HU1502200 \$303	.85
2"	buttweld	15000	HU1502200BW NEW 352	.25
3"	threaded	15000	HU1502300 670.	.00
3"	buttweld	15000	HU1502300BW NEW 730.	.30
4"	threaded	15000	HU1502400 1060.	.50
4"	buttweld	15000	HU1502400BW NEW 1268	.05



R