

BALDOR® • RELIANCE

Product Information Packet

IDXM7542T

3HP,1755RPM,3PH,60HZ,182TC,0632M,XPFC,F1

Part Detail							
Revision:	E	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:	0632M	Elec. Spec:	06WGX181	CD Diagram:	CD0005
Enclosure:	XPFC	Mfg Plant:		Mech. Spec:	06J010	Layout:	06LYJ010
Frame:	182TC	Mounting:	F1	Poles:	04	Created Date:	12-21-2011
Base:	RG	Rotation:	R	Insulation:	F	Eff. Date:	08-19-2013
Leads:	9#16					Replaced By:	
Literature:		Elec. Diagram:					

Nameplate NP0890XPSL							
NO.		CC	010A				
S/N		TEMP CODE	T2B				
SPEC.	06J010X181G2	INV.TYPE	PWM				
CAT.NO.	IDXM7542T	C HP FR	60	C HP TO	90		
HP	3	CT HZ FROM	6	CT HZ TO	60		
VOLTS	230/460	VT HZ FROM	6	VT HZ TO	60		
AMPS	8.2/4.1	MAG CUR	4.2/2.1				
RPM	1755	MX RPM	2700				
HZ	60	PH	3	CL	F	NOM.EFF.	89.5
SER.F.	1.00	DES	B	SL HZ	1.5	WK2	0.3
FRAME	182TC	RATING	40C AMB-CONT				
	75C RISE						

Parts List		
Part Number	Description	Quantity
SA236472	SA 06J010X181G2	1.000 EA
RA223419	RA 06J010X181G2	1.000 EA
36FN3000C01SP	EXFN, PLASTIC, 5.25 OD, .912 ID	1.000 EA
HW3201A05	3/8-16 EYEBOLT	1.000 EA
07CB1000A02	CONDUIT BOX, MODEL 306,EXP. PROOF	1.000 EA
10XN2520A12	O1/4-20X 3/4 HEX HEAD CAP	4.000 EA
HW1001A25	LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I	4.000 EA
WD1000B17	T&B CX35TN TERMINAL	1.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
HW4500A19	1/4-28X1/4 SLOTTED PLUG F/S	2.000 EA
06EP1706A01	SPECIAL FRONT ENDPLATE X06M - TEFC	1.000 EA
10XN3118K20	5/16-18 X 1 1/4 GRADE 5 STEEL ZC PLATED	4.000 EA
HW1001A31	LOCKWASHER 5/16, ZINC PLT.591 OD, .319 I	4.000 EA
HW5100A05	WVY WSHR F/205 & 304 BRGS	1.000 EA
06EP1707A01	STD XP PU EP 182-4TC 206 BRG 306M	1.000 EA
51XN1032A20	10-32 X 1 1/4 HX WS SL SR	2.000 EA
HW4001A01	1/4 HX SOC PIPE PLG (F/S) ALLOY STEEL W/	2.000 EA
60XN1032A07	10-32 X 1/2 TRUSS HEAD, TORX SERRATED ZN	2.000 EA
10XN3118K20	5/16-18 X 1 1/4 GRADE 5 STEEL ZC PLATED	4.000 EA
HW1001A31	LOCKWASHER 5/16, ZINC PLT.591 OD, .319 I	4.000 EA
06FH1003A01	FAN COVER, CAST X-PROOF--MACHINING	1.000 EA
51XN1032A14	10-32 X 0.875 HX WS SL SR	4.000 EA
07CB1500A01	CONDUIT BOX LID MACH	1.000 EA
10XN2520A16	1/4-20 X 1 HEX HEAD CAP SCR, ZINC PLATED	4.000 EA

Parts List (continued)		
Part Number	Description	Quantity
HW1001A25	LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I	4.000 EA
HW2501E16	3KEY, 1/4 SQ X 1.750	1.000 EA
HA7000A02	KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA	1.000 EA
LB1081	ALUM XP CAUTION LABEL	1.000 EA
LB1115N	LABEL,LIFTING DEVICE (ON ROLLS)	1.000 EA
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	6.000 EA
MJ1000A75	GREASE, POLYREX EM EXXON (USe 4824-15A)	0.050 LB
51XB1214A16	12-14X1.00 HXWSSLD SERTYB	1.000 EA
MG1025G29	MUNSELL 4.5Y 5.3/0.7 DARK CHARCOAL GREY	0.028 GA
MG1025Z20	ACTIVATOR WILKOFAS 060.32	0.010 GA
LB1119N	WARNING LABEL	1.000 EA
LB1125C01	STD (STOCK) CARTON LABEL BALDOR WITH FLA	1.000 EA
LC0145B01	CONNECTION LABEL	1.000 EA
NP0890XPSL	SS XP INV UL CSA CC CL-I GP-D	1.000 EA
G0PA1000	SPCL PACKAGING	1.000 EA
LB1506	LABEL "AMERICAN MADE" 1.50 X 1.00	1.000 EA
MN416A01	TAG-INSTAL-MAINT no wire (1200/bx) 10/13	1.000 EA

AC Induction Motor Performance Data

Page 1 of 1



AC Induction Motor Performance Data
 Record # 36483
 Typical performance - not guaranteed values

Winding: 06WGX181	Type: 0632M	Enclosure: TEBC
--------------------------	--------------------	------------------------

Nameplate Data			General Characteristics at 460 V, 60 Hz: High Volt Connection			
Rated Output (HP)	3		Full Load Torque	9.06 LB-FT		
Volts	230/460		Start Configuration	DOL		
Full Load Amps	8.2/4.1		Break Down Torque	33.1 LB-FT		
R.P.M.	1755		Pull-Up Torque	18.2 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque	20.4 LB-FT	
NEMA Design Code	B	KVA Code	J	Starting Current	29.8 Amps	
Service Factor	1			No-load Current	2.14 Amps	
NEMA Nom. Eff.	89.5	P.F.	77	Line-line Res. @ 25°C.	3.94 Ohms	
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	35°C	
S.F. Amps				Temp. Rise @ S.F. Load		

Load Characteristics at 460 Volts, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	38	58	70	77	81	83	
Efficiency	83.2	88.3	89.8	89.7	89.1	87.7	
Speed	1790	1779	1769	1757	1744	1730	
Line Amperes	2.34	2.79	3.39	4.1	4.91	5.86	

Baldor Electric Company Fort Smith, Arkansas







