


## Vent-Lock™ Safety Cam and Groove Couplings

**Application:**

- transfer of fluids and solids, with a safer disconnection

**Features:**

- safety release cam and groove couplings permit the release of static pressure when disconnecting hose assemblies
- venting system protects operator from being sprayed with hazardous or non-hazardous fluids or solids
- rated to **250 PSI**, recommendation based on the use of mating Dixon™ L-style fittings at ambient temperature **70°F (21°C)** with standard Buna-N seal installed, for use at elevated temperature or other unusual operating conditions, consult Dixon™
  - 1", 1½" and 2" sizes have a maximum working pressure of **250 PSI**
  - 3" maximum working pressure **150 PSI** with King Crimp™ ferrules, crimp sleeves and bands at **125 PSI**
- does not interchange with standard cam and groove products use only with Dixon™ L-style fittings 
- safety orange cam arms
- consult Dixon™ for availability of other materials

**Attachment Options:**

- ferrules, sleeves, bands, and other reliable options

### Type A Adapter x Female NPT

Size	316 Stainless Steel	
	Part #	Price/E
1"	<b>L100-A-SS</b>	<b>\$54.35</b>
1½"	<b>L150-A-SS</b>	<b>56.10</b>
2"	<b>L200-A-SS</b>	<b>69.30</b>
3"	<b>L300-A-SS</b>	<b>132.00</b>



### Type C Coupler x Hose Shank

Size	316 Stainless Steel	
	Part #	Price/E
1"	<b>L100-C-SS</b>	<b>\$87.25</b>
1½"	<b>L150-C-SS</b>	<b>130.00</b>
2"	<b>L200-C-SS</b>	<b>125.70</b>



### EZ Boss-Lock™ Type C Coupler x Hose Shank

Size	type C 316 Stainless Steel	
	Part #	Price/E
1"	<b>RLC100EZ</b>	<b>\$119.65</b>
1½"	<b>RLC150EZ</b>	<b>126.50</b>
2"	<b>RLC200EZ<sup>1</sup></b>	<b>157.80</b>
3"	<b>RLC300EZ<sup>1</sup></b>	<b>240.95</b>



<sup>1</sup> has drop shank