

BALDOR® • RELIANCE

Product Information Packet

L5026

1HP,1140RPM,1PH,60HZ,184,X3634L,XPFC,F1

Part Detail							
Revision:	AF	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:	3634L	Elec. Spec:	36WG0608	CD Diagram:	CD0001
Enclosure:	XPFC	Mfg Plant:		Mech. Spec:	36N007	Layout:	36LYN007
Frame:	184	Mounting:	F1	Poles:	06	Created Date:	
Base:	RG	Rotation:	R	Insulation:	B	Eff. Date:	08-15-2013
Leads:	6#16					Replaced By:	
Literature:		Elec. Diagram:					

Nameplate NP1426XPSL					
NO.		CC			
SER.					
SPEC.	36N07-608				
CAT.NO.	L5026				
HP	1	T. CODE	T3C		
VOLTS	115/208-230				
AMPS	14/7.4-7				
RPM	1140				
HZ	60	PH	1	CL	B
SER.F.	1.00	DES	L	CODE	K
RATING	40C AMB-CONT				
FRAME	184	NEMA-NOM-EFF	67		
USABLE AT 208V		PF	67		
BLANK					

Parts List		
Part Number	Description	Quantity
SA037351	SA 36N07-608	1.000 EA
RA033376	RA 36N07-608	1.000 EA
EC1324A03	ELEC CAP, 324-389 MFD, 125V, 1.81D X 3.	2.000 EA
35CB3001A02SP	EXPL PROOF CONDUIT BOX, 3/4"PIPE TAP LEA	1.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
HW3001B01	003SS CUP WASHER, FOR #8 SCREW	1.000 EA
36EP3700A01	FR ENDPLATE, MACH	1.000 EA
HW4500A19	1/4-28X1/4 SLOTTED PLUG F/S	2.000 EA
13XF0832A08	8-32 X.50 PAN HD,SLTD, TYPE F SCREW, ZIN	2.000 EA
HW5100A05	WVY WSHR F/205 & 304 BRGS	1.000 EA
36EP3701A01	PU ENDPLATE, MACH	1.000 EA
HW4500A19	1/4-28X1/4 SLOTTED PLUG F/S	2.000 EA
XY3816A12	3/8-16 FINISHED NUT	4.000 EA
36FH4009A02	FAN COVER FOR VM7042T	1.000 EA
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 EA
35CB3500A01SP	CONDUIT BOX LID, MACH	1.000 EA
51XN2520A16	SCREW, HEX WS SLT, ZN, 1/4-20 X 1.00	4.000 EA
HW2501D13SP	KEY, 3/16 SQ X 1.375	1.000 EA
NP0018	NP- XP CONDUIT BOX DO NOT MAKE SELLABLE	1.000 EA
HA7000A01	KEY RETAINER 7/8" DIA SHAFT	1.000 EA
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	6.000 EA
HA6003A52	CLAMP, CAPACITOR, WHITE ZINC PLATED	2.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 EA
MJ1000A75	GREASE, POLYREX EM EXXON (USe 4824-15A)	0.050 LB

Parts List (continued)		
Part Number	Description	Quantity
36FN3000A01SP	EXFN, PLASTIC, 7.00 OD, .912 ID	1.000 EA
51XB1214A16	12-14X1.00 HXWSSLD SERTYB	1.000 EA
MG1025Z20	ACTIVATOR WILKOFAS 060.32	0.010 GA
MG1025G29	MUNSELL 4.5Y 5.3/0.7 DARK CHARCOAL GREY	0.022 GA
HA3105A06	THRUBOLT- 3/8-16 X 10.500 X	4.000 EA
SP5061A08	MODEL 36 XP TYPE L/LC	1.000 EA
LB1119N	WARNING LABEL	1.000 EA
LB1125C01	STD (STOCK) CARTON LABEL BALDOR WITH FLA	1.000 EA
LC0081	CONNECTION LABEL X	1.000 EA
NP1426XPSL	SS XP UL CSA CC CL-I GP-D CL-II GP-F&G	1.000 EA
36PA1001	PACKAGING GROUP	1.000 EA
LB1506	LABEL "AMERICAN MADE" 1.50 X 1.00	1.000 EA
MN416A01	TAG-INSTAL-MAINT no wire (1200/bx) 10/13	1.000 EA

AC Induction Motor Performance Data

Record # 10489 - Typical performance - not guaranteed values

Winding: 36WG0608-R005	Type: 3634L	Enclosure: XPFC
-------------------------------	--------------------	------------------------

Nameplate Data				230 V, 60 Hz: High Voltage Connection	
Rated Output (HP)	1			Full Load Torque	4.6 LB-FT
Volts	115/208-230			Start Configuration	direct on line
Full Load Amps	14/7.4-7			Breakdown Torque	8.5 LB-FT
R.P.M.	1140			Pull-up Torque	7.9 LB-FT
Hz	60	Phase	1	Locked-rotor Torque	12 LB-FT
NEMA Design Code	L	KVA Code	K	Starting Current	34 A
Service Factor (S.F.)	1			No-load Current	4.85 A
NEMA Nom. Eff.	67	Power Factor	67	Line-line Res. @ 25°C	0.502 Ω A Ph 1.74 Ω B Ph
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	74°C

Load Characteristics 230 V, 60 Hz, 1 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	34	48	59	67	73	76
Efficiency	47.8	62.6	68.5	70.6	70.4	68.3
Speed	1188	1178	1168	1155	1140	1119
Line amperes	5.05	5.4	6	6.85	7.95	9.4

Performance Graph at 230V, 60Hz, 1.0HP Typical performance - Not guaranteed values





