

Series 1 Oil-Fog Lubricators


Applications:

- Oil-fog lubricators, identified by a green adjusting screw, are used for lubricating a single air tool or air motor and should be installed as near the device as possible.

Features:

- all the oil visible dropping through the transparent sight-feed dome goes to the airstream
- L72C, L73C and L74C OIL-FOG lubricators can be filled under pressure
- in-line or modular installation
- quick release bayonet bowl
- can be filled under pressure
- recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F
- maximum operating conditions:
 - transparent bowl: **150 PSI** and **125°F**
 - metal bowl: **250 PSI** and **175°F**

F




- Feature:**
- 2 oz. reservoir

Sub-Compact

Port Size	Flow (SCFM)	Transparent Bowl		Metal Bowl	
		Part #	Price/E	Part #	Price/E
1/4"	51	L72C-2	\$104.55	L72C-2MB	\$122.10
3/8"	51	L72C-3	109.35	L72C-3MB	125.90



with transparent bowl




- Feature:**
- 4 oz. reservoir

Compact

Port Size	Flow (SCFM)	Transparent Bowl		Metal Bowl	
		Part #	Price/E	Part #	Price/E
1/4"	60	L73C-2	\$142.55	L73C-2MB	\$150.50
3/8"	60	L73C-3	142.55	L73C-3MB	151.95
1/2"	60	L73C-4	142.40	L73C-4MB	150.50



with metal bowl



- Features:**
- 7 oz. reservoir

Standard

Port Size	Flow (SCFM)	Transparent Bowl		Metal Bowl	
		Part #	Price/E	Part #	Price/E
3/8"	118	L74C-3	\$180.45	L74C-3MB	\$183.55
1/2"	192	L74C-4	178.75	L74C-4MB	180.95
3/4"	186	L74C-6	178.75	L74C-6MB	183.55



metal bowl

See pages 258-259 for lubricator accessories. See page 149 for air tool lubricant.



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings given at 90 PSIG inlet pressure.