

Footnotes

| | | | |
|----|---|----|---|
| S | Steel frame | 26 | Shaft is 1/2" Dia. X 1 1/2" long with flat |
| A | Aluminum frame | 27 | Shaft is 5/8" Dia. X 1.97" long with 3/16" keyway |
| C | Cast Iron frame | 28 | 1/4" long extended through-bolts |
| US | Made in the USA | 29 | IEC Frame - See IEC dimension chart in back of catalog for dimension information |
| MX | Made in Mexico | 30 | CW rotation only, from lead end of motor |
| CA | Made in Canada | 31 | For motors having a "P" suffix letter in the date code |
| CN | Made in China | 32 | Motor has terminal board connection |
| 2 | These combination 56H base motors have mounting holes for 56 and 143-5T, and 1/2 diameter shaft with flat 1.5" long | 33 | Automatic overload - cannot use with VFD |
| 3 | Combination 56 H base has mounting holes for NEMA 56 and 143-5T and a standard NEMA 145T frame shaft of 7/8" Dia. | 34 | 1" long extended through-bolts |
| 4 | These motors have a NEMA 215T base mounting pattern and shaft height of 5.25", with usable length of 3 3/8 and diameter of 1 1/8 with standard key | 35 | Terminal studs at 12:00 |
| 5 | Combination 56 H base has mounting holes for NEMA 56, and has a standard NEMA 145T frame shaft of 7/8" Dia. | 36 | Special BA dimension 2.31 for belt guard clearance |
| 6 | Combination 56H base has mounting holes for NEMA 56 and NEMA 143-5T and a standard NEMA 56 shaft of 5/8" | 37 | Uses drip cover kit 175305.00 |
| 7 | 48YZ motors have std. 48-frame base with 1/2" dia. X 1 7/8 long shaft ext. with flat. Also includes sleeve to convert shaft to 5/8" dia. With 3/16" square key" | 38 | Uses drip cover kit 175004.00 |
| 8 | NEMA 145TC shaft, 7/8" X 2 1/4" and NEMA 56 removable base | 39 | Uses drip cover kit 175932.00 |
| 9 | S56CZ motors have mounting bases with NEMA 56 mounting holes, NEMA 56/143-5T C-face and a NEMA 143-5T shaft extension (7/8" dia x 2 1/4" long) | 40 | Uses drip cover kit 175933.00 |
| 10 | Motor has mounting base with 182T mounting holes, shaft height is 4.5". Shaft is std. NEMA 56-5/8" dia. X 1 7/8 long | 41 | Uses drip cover kit 175846.00 |
| 11 | TEBC totally enclosed blower cooled | 42 | Uses drip cover kit 175849.00 |
| 12 | TENV totally enclosed non-vented | 43 | Uses drip cover kit 175962.00 |
| 13 | TEFC totally enclosed fan cooled | 44 | Uses drip cover kit 175963.00 |
| 14 | F1 mounting only | 45 | Uses drip cover kit 175614.00 |
| 15 | Built-in conduit box located at 12:00 | 46 | 50 Hz operation at rated HP |
| 16 | 1/2" diameter shaft - 2 1/4" long | 47 | Rated at 50Hz at full rated HP |
| 17 | 5/8" diameter shaft - 2 5/8" long | 48 | 190/380V, 50Hz at next lowest HP @1.15 S.F. |
| 18 | Shaft extension has keyway and flat 180° apart for ease of mounting | 49 | Class F insulated |
| 19 | Shaft is 5/8" Dia.by 2.0" long | 50 | Suitable for single speed operation only |
| 20 | Shaft is 5/8" Dia.by 2 5/8" long | 51 | Mechanical centrifugal starting switch with overspeed protection, others have electronic start switch |
| 21 | Shaft is 3/4" Dia.by 3 1/2" long | 52 | Extra high starting torque |
| 22 | Standard 5/8" diameter shaft with keyway plus 3/4" deep hole drilled and tapped to 1/4-20 UNC in end of shaft to facilitate mounting of some fan blades | 53 | Capacitor start/capacitor run design for reduced amperage, others are capacitor start/induction run |
| 23 | Standard 7/8" diameter shaft with keyway plus 3/4" deep hole drilled and tapped to 1/4-20 UNC in end of shaft to facilitate mounting of some fan blades | 54 | Split phase start, capacitor run is suitable for belt drive within the airflow of the fan |
| 24 | Motor's shaft is 1 inch longer than standard | 55 | Split phase start, capacitor run |
| 25 | Shaft extension has keyway and flat 180° apart for ease of mounting. Useable shaft is 1 1/2" long by 1/2 Dia., 1/8" keyway | 56 | Designed for inverter duty operation |
| | | 57 | Rated for farm duty service |
| | | 58 | Provision for belly band mount, no base |
| | | 59 | Resilient base with provision for belly band mount |
| | | 60 | Rigid base |
| | | 61 | Nema 145TC face mounting with removable NEMA 182T rigid base |
| | | 62 | Provision for belly band and pedestal fan mounting, no rigid base |
| | | 63 | Resilient base |