



NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	C	AG	2F	2FF	2FFF	BS
1375	284TSC	25.13	22.13	9.50			1.69
1525	286TSC	26.63	23.63	11.00	9.50	9.50	1.69

				TOLERANCES UNLESS SPECIFIED		Lincoln MOTORS		DRAWN NJS 03-11-2003	
				DEC.	INCHES			CHK	ML
3	REV'D BS DIM IN TABLE 1.69 WAS 1.19 ECO 0038336	DRO 09-18-2013	EMH .XX	±.03		TITLE OUTLINE 280TSC TEFC UEI		APPD	TB
2	ADDED "HOLE FOR $\phi .75$ CONDUIT" CN 38428	HLB 09-28-2004	ML .XXX	±.005				SCALE	1=4
1	NEW DRAWING	NJS 03-12-2003	TB .XXXX	±.0005				REF	
NO.	REVISION	BY & DATE	CHK	ANG	FINISH	CAD FILE xf5f1sc2		PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP		SIZE	DRAWING NO.
						DIST LB		B	XF5F1SC2
								PAGE	OF
								3	