




Factory Set Pressure Reducing Brass Angle Valves

Valves

Features:

- true combination shut-off and pressure reducing valves
- 1½" reduces inlet pressure of 300 PSI (2069 kPa) or less to working pressures of **10** through **175 PSI** (69-1207 kPa); 2½" reduces inlet pressures of 400 PSI (2758 kPa) or less to working pressures of **20** through **175 PSI** (138-1207 kPa) under discharge or static conditions
- female x female valves have an open / closed indicator bonnet for confirmation of status
- tamper resistant and automatic
- available with a tamper proof switch
- all debris must be flushed from the system prior to being placed into service 
- complete switch, bracket and housing available for field mounting, consult Dixon® for price and availability
- other configurations are available, contact Dixon® for additional information

Specifications:

- UL listed for Automatic Sprinkler Systems as floor or zone control valves
- Standpipe Systems, Class I, II and III
- Automatic Check Valve for Dual Riser Systems
- Approved by New York City Board of Standards and Appeals, approval # MEA 54-07-E
- Approved by City of Los Angeles and the City of San Francisco (ULC 2½")



Female x Male


Inlet Female NPT	Outlet Male NST (NH)	Cast Brass	
		Part #	Price/E
1½"	1½"	NAPRAV150F-15	\$720.00
		NAPRAV150F-20	720.00
		NAPRAV150F-25	720.00
		NAPRAV150F-30	720.00
		NAPRAV150F-35	720.00
2½"	2½"	NAPRAV250F-55	940.00
		NAPRAV250F-60	940.00
		NAPRAV250F-65	940.00
		NAPRAV250F-70	940.00
		NAPRAV250F-75	940.00
		NAPRAV250F-80	940.00

Female x Female

Inlet Female NPT	Outlet Female NPT	Cast Brass	
		Part #	Price/E
1½"	1½"	NAPRAVF150-15	\$720.00
		NAPRAVF150-20	720.00
		NAPRAVF150-25	720.00
		NAPRAVF150-30	720.00
		NAPRAVF150-50	720.00
2½"	2½"	NAPRAVF250-55	940.00
		NAPRAVF250-60	940.00
		NAPRAVF250-65	940.00
		NAPRAVF250-70	940.00
		NAPRAVF250-75	940.00
		NAPRAVF250-80	940.00



Dimensions



Size	A	B	C	D	E closed	E open
1½"	2-7/32"	4-5/32"	3 7/8"	3 3/4"	9-25/64"	8-53/64"
2½"	3-7/32"	6-3/32"	5 3/4"	5 3/4"	11 1/8"	10-13/16"