

## FLEX CONNECTORS SCREW-IN TYPE

**Features:**

- Zinc Die Cast



| Cat. No. | Trade Size | Std. Pkg. | Master Ctn. |
|----------|------------|-----------|-------------|
| OF671    | 3/8"       | 100       | 1000        |
| OF672    | 1/2"       | 100       | 1000        |
| OF673    | 3/4"       | 100       | 500         |
| OF674    | 1"         | 25        | 250         |
| OF675    | 1-1/4"     | 10        | 100         |
| OF681    | 1-1/2"     | 5         | 50          |
| OF682    | 2"         | 3         | 30          |

## INSULATED FLEX CONNECTORS SCREW-IN TYPE

**Features:**

- Zinc Die Cast
- With Insulated Throat



**Note:**

- Insulated color may vary

| Cat. No. | Trade Size | Std. Pkg. | Master Ctn. |
|----------|------------|-----------|-------------|
| OF671-S  | 3/8"       | 100       | 1000        |
| OF672-S  | 1/2"       | 100       | 1000        |
| OF673-S  | 3/4"       | 100       | 500         |
| OF674-S  | 1"         | 25        | 250         |
| OF675-S  | 1-1/4"     | 10        | 100         |
| OF681-S  | 1-1/2"     | 5         | 50          |
| OF682-S  | 2"         | 3         | 30          |

## FLEX COUPLINGS SCREW-IN TYPE

**Features:**

- Zinc Die Cast



| Cat. No. | Trade Size | Std. Pkg. | Master Ctn. |
|----------|------------|-----------|-------------|
| OF676    | 1/2"       | 100       | 1000        |
| OF677    | 3/4"       | 100       | 500         |
| OF678    | 1"         | 25        | 250         |
| OF679    | 1-1/4"     | 10        | 100         |
| OF685    | 1-1/2"     | 5         | 50          |
| OF686    | 2"         | 3         | 30          |

## FLEX BUSHING

**Features:**

- Steel
- Electroplated Zinc
- Used to insulate Cut Flex when the conduit is used for data cables without a junction box



*Shown Installed*

| Cat. No. | Trade Size | Std. Pkg. | Master Ctn. |
|----------|------------|-----------|-------------|
| FB-50    | 1/2"       | 100       | 1000        |
| FB-75    | 3/4"       | 100       | 500         |
| FB-100   | 1"         | 25        | 250         |