


Series 1 Miniature FRL's

- 5 micron element
- 1 oz. reservoir
- inlet pressure **150 PSI** maximum at ambient temperature (70°F)

Miniature Filter with Transparent Bowl

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/8"	19	F07-100A	\$68.55	F07-100M	\$58.80
1/4"	24	F07-200A	66.95	F07-200M	57.40




** minimum clearance to remove bowl

- pressure range 5-100 PSI
- relieving type
- inlet pressure **300 PSI** maximum at ambient temperature (70°F)
- regulation at flows up to 22 SCFM at 100 PSIG
- RG models supplied with a GC620 gauge
- panel nut not included

Miniature Regulators


Port Size	Flow (SCFM)	with Gauge		without Gauge	
		Part #	Price/E	Part #	Price/E
1/8"	14	R07-100RG	\$61.20	R07-100R	\$44.50
1/4"	15	R07-200RG	60.75	R07-200R	44.05



- pressure range 5-100 PSI
- relieving type
- 5 micron element
- 1 oz. reservoir
- push to lock adjusting knob
- inlet pressure **150 PSI** maximum at ambient temperature (70°F)
- supplied with a GC620 gauge
- bowl guard not available

Miniature Filter/Regulator with Transparent Bowl

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/8"	13	B07-102AG	\$124.45	B07-102MG	\$113.45
1/4"	24	B07-202AG	122.50	B07-202MG	112.10




** minimum clearance to remove bowl

- 1 oz. reservoir
- inlet pressure **150 PSI** maximum at ambient temperature (70°F)

Miniature Lubricators

Port Size	Flow (SCFM)	Transparent Bowl	
		Part #	Price/E
1/8"	10	L07-100A	\$88.85
1/4"	14	L07-200A	87.55




** minimum clearance to remove bowl

- pressure range 5-125 PSI
- 1 oz. reservoir
- supplied with a GC620 gauge
- inlet pressure **150 PSI** maximum at ambient temperature (70°F)

Miniature Combination Unit with Transparent Bowl

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/8"	10	P1A-100A	\$263.80	P1A-100M	\$254.05
1/4"	14	P1A-200A	261.00	P1A-200M	251.45




** minimum clearance to remove bowl

Series 1 Micro Mate Combination Units

- pressure range 5-125 PSI
- requires only 2 pipe connections
- inlet pressure **150 PSI** maximum at ambient temperature (70°F)

Miniature Filter/Regulator/Lubricator with Transparent Bowl

Port Size	Flow (SCFM)	Automatic Drain	
		Part #	Price/E
1/8"	10	PTH-100AG	\$234.60
1/4"	14	PTH-200AG	246.45



** minimum clearance to remove bowl



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure for regulators, 90 PSIG all others.

F