

Caps and Plugs

Breakable Cap

**Application:**


- prevents entry of foreign material and protects female threads on pin lug fire department inlet connections

Feature:

- used on pin lug females

| Size | Polycarbonate | | Wt. Lbs. |
|------|---------------|---------------|----------|
| | Part # | Price/E | |
| 2½" | PBC250 | \$8.00 | 0.13 |

Aluminum Breakable Cap

**Features:**

- for use on fire department inlet connections
- prevents entry of foreign matter and protects female threads
- breakable ears feature permits fast hose connection
- two eyebolts with nuts for attachment to female pin lug swivel
- painted red finish

| Size | Aluminum | | Wt. Lbs. |
|------|---------------|----------------|----------|
| | Part # | Price/E | |
| 2½" | ABC250 | \$10.90 | 0.24 |

Red FDC Plug

**Features:**

- fits standard 2½" NST female swivel
- withstands wide range of temperatures from **-4°F to 200°F (-20°C to 93°C)**
- 1⅝" pentagonal nut with weep hole to allow for drainage
- removed from FDC with adjustable hydrant wrench

| NST (NH) Thread | Polycarbonate | | Wt. Lbs. |
|--------------------|---------------|----------------|----------|
| | Part # | Price/E | |
| 2½" | PP250F | \$12.00 | 0.02 |

Adjust-A-Plug

**Features:**

- molded red polycarbonate protective plug for swivel connections up to 2½"
- two adjustable metal plates installed in the back of the plug can be mated with your local thread
- plug can be easily removed with a fire department spanner wrench

| Polycarbonate | | Wt. Lbs. |
|---------------|---------------|----------|
| Part # | Price/E | |
| PAP250 | \$8.00 | 0.24 |