

Contractor Pressure Gauges

Features:

- accuracy class: $\pm 1\%$ of span
- wetted parts: copper alloy
- window: acrylic, snap in



4277768-0001

- dial: aluminum, white
- pointer: aluminum, black, adjustable
- mounting flanged/bracket; rear flange: stainless steel
- case: stainless steel

4½" face

¼" lower mount

PSI Range	Part #	Price/E
0-15	4277750-0001	\$71.60
0-30	4277768-0001	71.60
0-60	4277776-0003	71.60

F

FlutterGuard™ Dry Gauges

Features:

- FlutterGuard™ virtually eliminates pointer flutter, making the gauge easier to read and reducing excessive movement wear. Liquid-free casing results in lighter weight and eliminates the chance of gauge leakage.
- ASME B40.1, Grade B ($\pm 3-2-3\%$ accuracy)
- ABS plastic case
- C-shaped bronze safety bourdon tube (600 PSI gauges and lower)
- helical wound bronze safety bourdon tube (1000 PSI gauges and higher)
- polycarbonate crystal
- black aluminum pointer
- PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.
- ambient temperature range of **-40°F to 150°F**



GL350FG

2½" face

¼" lower mount

PSI Range	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	1	.5	GL300FG	\$22.20
0-30	5	.5	GL320FG	20.70
0-60	5	1	GL325FG	20.70
0-100	10	2	GL330FG	20.70
0-160	20	5	GL335FG	20.70
0-200	20	5	GL340FG	20.70
0-300	30	5	GL345FG	20.70
0-400	50	10	GL347FG	20.70
0-600	50	10	GL350FG	20.70
0-1000	200	20	GL355FG	29.85
0-1500	300	50	GL360FG	29.85
0-2000	400	50	GL365FG	29.85
0-3000	500	100	GL370FG	29.85
0-5000	1000	100	GL375FG	29.85

Stainless Panel Builder Gauges

Applications:

- fits industry standard 2.56" panel hole cutout
- suitable for corrosive environments
- used in gaseous and liquid media

Features:

- ASME B40.100 Grade A 2/1/2% full scale accuracy
- 316L stainless steel wetted parts
- white aluminum with black lettering; stop pin
- black aluminum pointer
- glycerin filled case
- laminated safety glass window lens
- temperature range: **-4°F to 140°F**
- maximum media temperature **212°F** maximum



PBLSS200

2½" face

¼" lower back mount

PSI Range	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	3	.2	PBLSS15	\$151.60
0-30	5	.5	PBLSS30	151.60
0-60	10	1	PBLSS60	151.60
0-100	20	2	PBLSS100	151.60
0-160	20	2	PBLSS160	151.60
0-200	50	5	PBLSS200	151.60
0-300	50	5	PBLSS300	151.60
0-400	100	10	PBLSS400	151.60
0-600	100	10	PBLSS600	151.60
0-800	200	20	PBLSS800	151.60
0-1000	200	20	PBLSS1000	151.60
0-1500	300	20	PBLSS1500	151.60
0-2000	500	50	PBLSS2000	151.60
0-3000	500	50	PBLSS3000	151.60
0-5000	1000	100	PBLSS5000	151.60