

BALDOR® • RELIANCE

Product Information Packet

PL1313M

1.5HP,3450RPM,1PH,60HZ,56/56H,3520LC

Part Detail							
Revision:	AL	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:	3520LC	Elec. Spec:	35WGY686	CD Diagram:	CD0320
Enclosure:	OPEN	Mfg Plant:		Mech. Spec:	35K352	Layout:	35LYK352
Frame:	56/56H	Mounting:	F1	Poles:	02	Created Date:	06-22-2007
Base:	RG	Rotation:	R	Insulation:	B	Eff. Date:	08-10-2012
Leads:	4#16 A&J,2#18 B PH,1#14 #4TH					Replaced By:	
Literature:		Elec. Diagram:					

Nameplate NP1257L										
CAT.NO.	PL1313M									
SPEC.	35K352Y686									
HP	1.5									
VOLTS	115/230									
AMP	13.2/6.6									
RPM	3450									
FRAME	56/56H	HZ			60	PH		1		
SER.F.	1.15	CODE			F	DES		L	CL	B
NEMA-NOM-EFF	75.5	PF			98					
RATING	40C AMB-CONT									
CC		USABLE AT 208V								
DE	6205	ODE			6203					
ENCL	OPEN	SN								

Parts List		
Part Number	Description	Quantity
SA026319	SA 35K352Y686	1.000 EA
RA022369	RA 35K352Y686	1.000 EA
OC3060C09	CYL OIL CAP 60MFD/240V	1.000 EA
TPMST24AB	THERMAL 1PH 0.75 MAN 120CREF- TPMSJ24AB	1.000 EA
EC1340A03SP	ELEC CAP, 340-408 MFD, 125V, 1.81D X 3.	1.000 EA
WD3006A01	RSS-2-103JT 2W 10K RES. METAL OXIDE 5%	1.000 EA
TP5059	GENERIC THERMAL KIT	1.000 EA
NS2512A01	INSULATOR, CONDUIT BOX X	1.000 EA
35CB3007A37	35 CB .88 DIA @ 6:00, .75 MTO @ 3:00	1.000 EA
36GS1000SP	GASKET-CONDUIT BOX, .06 THICK #SV-330 LE	1.000 EA
51XB1016A07	10-16 X 7/16 HXWSSLD SERTYB	2.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
HA6001A01	THERMAL RETAINER (PLATED)	1.000 EA
51XB1214A10	12-14 X 5/8HX WS SL SR TYBX	2.000 EA
35EP3201A03	STD FR EP OPEN-203BRG-35L OR M FRAME--LE	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 EA
35CB3801SP	CAPACITOR COVER, CAST	1.000 EA
HA7010	CAPACITOR RETENTION CLAMP	1.000 EA
NS2501A02	INSULATOR, CAPACITOR BOX	1.000 EA
51XB1016A08	10-16X 1/2HXWSSLD SERTYB	2.000 EA
HW5100A03SP	WAVY WASHER (W1543-017)	1.000 EA
35EP3200A02	STD PU ENDPLATE-OPEN-205 BRG	1.000 EA
XY1032A02	10-32 HEX NUT DIRECTIONAL SERRATION	4.000 EA
35CB4521	35 LIPPED CB LID (GALV & PHOSPH)	1.000 EA

Parts List (continued)		
Part Number	Description	Quantity
35GS1030	35 GS FOR CB LID - LEXIDE	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	4.000 EA
HW2501D13SP	KEY, 3/16 SQ X 1.375	1.000 EA
HA7000A04	KEY RETAINER 0.625 DIA SHAFTS	1.000 EA
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 EA
LB1087	LABEL,MANUAL RESET (ROLL LABEL)	1.000 EA
MJ1000A75	GREASE, POLYREX EM EXXON (USe 4824-15A)	0.050 LB
MG1000G27	MED CHARCOAL METALLIC GREY	0.017 GA
NP1257L	ALUM UL CSA CC THERMAL REV MTG	1.000 EA
HA3100A18	THRUBOLT 10-32 X 9.250	4.000 EA
SP5181A28	MODEL 35 LC TORQ STAT SWITCH LEAD ASSY	1.000 EA
WD1000A15	3-520132-2 AMP FLAG (4M/RL NON-CANC/NON-	4.000 EA
LB1119N	WARNING LABEL	1.000 EA
LB1125C01	STD (STOCK) CARTON LABEL BALDOR WITH FLA	1.000 EA
LC0269	1PH,DV,REV,THERMAL,7 LD,L.AMP THRU HTR H	1.000 EA
35PA1066	PACKING GROUP COMBINED PRINT	1.000 EA
LB1506	LABEL "AMERICAN MADE" 1.50 X 1.00	1.000 EA

Accessories		
Part Number	Description	Multiplier
35-8764	C FACE KIT	A8
35EP1604A01SP	D-FLANGE KIT	A8

AC Induction Motor Performance Data

Record # 10289 - Typical performance - not guaranteed values

Winding: 35WGY686-R001	Type: 3520LC	Enclosure: OPEN
-------------------------------	---------------------	------------------------

Nameplate Data				230 V, 60 Hz: High Voltage Connection	
Rated Output (HP)	1.5			Full Load Torque	2.25 LB-FT
Volts	115/230			Start Configuration	direct on line
Full Load Amps	13.2/6.6			Breakdown Torque	4.63 LB-FT
R.P.M.	3450			Pull-up Torque	3.25 LB-FT
Hz	60	Phase	1	Locked-rotor Torque	4.25 LB-FT
NEMA Design Code	L	KVA Code	F	Starting Current	34.7 A
Service Factor (S.F.)	1.15			No-load Current	1.5 A
NEMA Nom. Eff.	75.5	Power Factor	98	Line-line Res. @ 25°C	2.38 Ω A Ph 1.84 Ω B Ph
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	40°C
S.F. Amps				Temp. Rise @ S.F. Load	47°C

Load Characteristics 230 V, 60 Hz, 1.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	87	90	96	98	97	96	98
Efficiency	51	71	74.5	75.5	74	70	75
Speed	3575	3550	3515	3490	3440	3370	3470
Line amperes	2.7	3.6	5	6.6	8.4	10.5	7.4

Performance Graph at 230V, 60Hz, 1.5HP Typical performance - Not guaranteed values





