


## In-Line Lubricators

### Features:

- protects portable or stationary air tools by efficiently oiling the tool mechanisms; each time an air tool is operated a fine mist of oil is injected into it along with the air from the compressor
- installation is recommended within 25' of the tool to be lubricated, refer to the arrow for proper air flow direction
- transparent sight disc allows visual inspection of oil level
- oil flow regulated by screwdriver screw adjustment, minimum flow rate is 30 SCFM
- not recommended for constant flow applications
- for reciprocating tools only
- type of oil to use: any petroleum-based, non-detergent light weight oil (SAE 10/150SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil, do not use any synthetic oil or oils containing additives or solvents
- see page 149 for air tool lubricant



F



NPT Size	Oil Capacity	Max. Working Pressure at ambient temperature (70°F)	Air Flow at 70 PSI	Aluminum	
				Part #	Price/E
½"	1.4 fluid ozs.	<b>500 PSI</b>	30 SCFM	<b>PL300</b>	<b>\$111.80</b>
¾"	3.7 fluid ozs.	<b>200 PSI</b>	70 SCFM	<b>PL400</b>	<b>116.90</b>
¾"	11.0 fluid ozs.	<b>300 PSI</b>	70 SCFM	<b>PL400L</b>	<b>145.00</b>
1"	16.0 fluid ozs.	<b>250 PSI</b>	100 SCFM	<b>PL500</b>	<b>193.40</b>

### Replacement Parts

Description	Part #	Price/E	Description	Part #	Price/E
(A) oil adjustment valve assembly	<b>851661</b>	<b>\$46.00</b>	(D) fill plug O-ring	<b>700013-214</b>	<b>\$2.00</b>
(B) valve gasket	<b>452531</b>	<b>2.75</b>	(E) sight disk	<b>452532</b>	<b>2.90</b>
(C) fill plug	<b>452525</b>	<b>14.00</b>	(F) sight disk seal	<b>700013-016</b>	<b>2.30</b>
			(G) sight disk lock nut	<b>452533</b>	<b>6.75</b>

## In-Line Air Filters

### Features:

- protects small air tools, such as impact wrenches, nut runners, grinders and screwdrivers
- all-anodized, compact housing
- install directly before the air tool
- maximum operating pressure: **500 PSI**
- temperature range: **35°F to 200°F**
- air flow: 140 SCFM
- male x female configuration
- standard 40 micron element ensures minimum pressure drop
- elements can be replaced quickly



Male NPT	Overall Length	Diameter	Weight Lbs.	Aluminum	
				Part #	Price/E
¾"	3-13/16"	1½"	.46	<b>9076M</b>	<b>\$75.00</b>

## In-Line Lubricator with Filter

### Feature:

- consists of **9076M** particle filter with 40 micron sintered bronze element and **PL400** (3.7 ounce) or **PL400L** (11.0 ounce) lubricator



NPT Size	Oil Capacity	Max. Work. Press. at ambient temp. (70°F)	Aluminum	
			Part #	Price/E
¾"	3.7 fluid ozs.	<b>200 PSI</b>	<b>PL400WF</b>	<b>\$197.10</b>
¾"	11.0 fluid ozs.	<b>300 PSI</b>	<b>PL400LWF</b>	<b>223.25</b>

## In-Line Lubricator Base

### Features:

- base can be fitted to any existing PL lubricator
- keeps lubricator from flipping or rolling over, ensuring that it provides continuous lubrication to the downstream air tool



lubricator is not included with the base

Used On	Aluminum	
	Part #	Price/E
leveling base for PL300	<b>LB300</b>	<b>\$15.00</b>
leveling base for PL400	<b>LB400</b>	<b>15.75</b>
leveling base for PL500	<b>LB500</b>	<b>16.00</b>