

### MSHA Approved Single Jacket Mine Fire Hose



**Specification:**

- approved by MSHA: Mine Safety and Health Administration for all mine fire protection applications

**Features:**

- outer construction: single jacket, synthetic flame resistant
- tube construction: flame resistant lining
- proof pressure: **500 PSI at 70°F (21°C)**
- service test pressure: **250 PSI at 70°F (21°C)**
- working pressure: **225 PSI at 70°F (21°C)**

Coupled with female and male aluminum rocker lug expansion ring couplings

Size	Thread	Length	Part #	Price/E
1½"	NST (NH)	50'	<b>SM515W50RAF</b>	<b>\$561.05</b>
	NPSH	50'	<b>SM515W50RAS</b>	<b>561.05</b>

### Double Jacket Potable Water Hose - Blue



**Features:**


- Liner is NSF approved for potable water, fittings are not, except for temporary / emergency drinking needs only.
- outer construction: double jacket, all polyester
- tube construction: thermoplastic
- proof pressure: **600 PSI at 70°F (21°C)**
- service test pressure: **300 PSI at 70°F (21°C)**
- working pressure: **270 PSI at 70°F (21°C)**

Coupled with female and male, brass or aluminum rocker lug, expansion ring couplings

Size	Thread	Length	Brass		Aluminum	
			Expansion Ring Part #	Price/E	Expansion Ring Part #	Price/E
1½"	NPSH	50'	<b>PW615B50RBS</b>	<b>\$514.75</b>	<b>PW615B50RAS</b>	<b>\$484.00</b>
		100'	<b>PW615B100RBS</b>	<b>959.20</b>	<b>PW615B100RAS</b>	<b>859.10</b>
	NST (NH)	50'	<b>PW615B50RBF</b>	<b>514.75</b>	<b>PW615B50RAF</b>	<b>484.00</b>
		100'	<b>PW615B100RBF</b>	<b>959.20</b>	<b>PW615B100RAF</b>	<b>859.10</b>
2½"	NPSH	50'	<b>PW625B50RBS</b>	<b>1019.35</b>	<b>PW625B50RAS</b>	<b>761.75</b>
		100'	<b>PW625B100RBS</b>	<b>1647.75</b>	<b>PW625B100RAS</b>	<b>1363.10</b>
	NST (NH)	50'	<b>PW625B50RBF</b>	<b>1019.35</b>	<b>PW625B50RAF</b>	<b>761.75</b>
		100'	<b>PW625B100RBF</b>	<b>1647.75</b>	<b>PW625B100RAF</b>	<b>1363.10</b>



### 500# All Polyester Rack Hose - UL Labeled



**Application:**

- for pin rack service / emergency fire fighting only, not to be used for washdown

**Features:**

- outer construction: single jacket, all polyester
- tube construction: clear thermoplastic
- proof pressure: **300 PSI at ambient temperature 70°F (21°C)**
- service test pressure: **150 PSI at ambient temperature 70°F (21°C)**
- working pressure: **135 PSI at ambient temperature 70°F (21°C)**
- Underwriters Listed

Coupled with female and male expansion ring couplings

Size	Coupling Type	Length	Folded		Coiled	
			Part #	Price/E	Part #	Price/E
1½"	combo lug, brass NST (NH)	50'	<b>R515U50CBF/F</b>	<b>\$274.95</b>	<b>R515U50CBF</b>	<b>\$274.95</b>
	combo lug, brass NST (NH)	100'	<b>R515U100CBF/F</b>	<b>486.85</b>	<b>R515U100CBF</b>	<b>486.85</b>
	combo lug, alum. NST (NH)	50'	<b>R515U50RAF/F</b>	<b>258.60</b>	<b>R515U50RAF</b>	<b>258.60</b>
	combo lug, alum. NST (NH)	100'	<b>R515U100RAF/F</b>	<b>458.20</b>	---	---