


## Wilkerson Compact Regulators




**Features:**

- 0-125 PSI adjusting range
- for 0-60 PSI adjusting range, add an L to the end of the part number
- self-relieving standard
- can be installed with the adjusting knob in any position
- To increase regulated pressure, pull adjusting knob up and turn clockwise. To reduce pressure, turn knob counter clockwise.
- two 1/4" NPT gauge ports standard on models without gauge, one 1/4" NPT gauge port standard on models with gauge - can be used for additional outlet ports
- models supplied without gauge use a GC230 gauge
- maximum operating conditions:  
**300 PSIG (20.7 bar) and 32°F to 150°F (0°C to 65.5°C)**

F

Size	Flow (SCFM)	With Gauge		Without Gauge	
		Part #	Price/E	Part #	Price/E
1/4"	71.5	<b>R16-02RG</b>	<b>\$120.25</b>	<b>R16-02R</b>	<b>\$99.55</b>
3/8"	80.5	<b>R16-03RG</b>	<b>120.25</b>	<b>R16-03R</b>	<b>99.55</b>
1/2"	88.0	<b>R16-04RG</b>	<b>120.25</b>	<b>R16-04R</b>	<b>99.55</b>




**Features:**

- 0-125 PSI adjusting range
- self-relieving standard
- can be installed with the adjusting knob in any position
- To increase regulated pressure, pull adjusting knob up and turn clockwise. To reduce pressure, turn knob counter clockwise.
- Two 1/4" NPT gauge ports located on the front and rear faces of the body; ports may be used as additional regulated ports or for pressure gauges.
- models supplied without gauge use a GC230 gauge
- maximum operating conditions:  
**300 PSIG (20.7 bar) and 32°F to 150°F (0°C to 65.5°C)**

Size	Flow (SCFM)	With Gauge		Without Gauge	
		Part #	Price/E	Part #	Price/E
1/4"	82	<b>R18-02RG</b>	<b>\$92.60</b>	<b>R18-02R</b>	<b>\$71.90</b>
3/8"	97	<b>R18-03RG</b>	<b>92.60</b>	<b>R18-03R</b>	<b>71.90</b>
1/2"	97	<b>R18-04RG</b>	<b>92.60</b>	<b>R18-04R</b>	<b>71.90</b>

## Wilkerson Standard Regulators



**Features:**

- 0-125 PSI adjusting range
- non-rising push/pull locking adjustment knob
- panel mount nut standard
- excellent flow characteristics
- can be installed with the adjusting knob in any position
- To increase regulated pressure, pull adjusting knob up and turn clockwise. To reduce pressure, turn knob counter clockwise.
- two 1/4" NPT gauge ports standard on models without gauge, one 1/4" NPT gauge port standard on models with gauge - can be used for additional outlet ports
- models supplied without gauge use a GC230 gauge
- maximum operating conditions:  
**300 PSIG (20.7 bar) and 32°F to 150°F (0°C to 65.5°C)**

Size	Flow (SCFM)	With Gauge		Without Gauge	
		Part #	Price/E	Part #	Price/E
1/4"	112	<b>R26-02RG</b>	<b>\$172.40</b>	<b>R26-02R</b>	<b>\$151.70</b>
3/8"	148	<b>R26-03RG</b>	<b>172.40</b>	<b>R26-03R</b>	<b>151.70</b>
1/2"	185	<b>R26-04RG</b>	<b>172.40</b>	<b>R26-04R</b>	<b>151.70</b>

See pages 229-231 for regulator accessories.



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure.