

500# All Polyester Rack Hose - Brass Couplings non-UL Labeled



folded



coiled

Application:

- for pin rack service / emergency fire fighting only, not to be used for washdown



Features:

- outer construction: single jacket, all polyester
- tube construction: clear thermoplastic
- proof pressure: **500 PSI** at ambient temperature (70°F)
- service test pressure: **250 PSI** at ambient temperature (70°F)
- working pressure: **225 PSI** at ambient temperature (70°F)

Coupled with female and male brass combo lug expansion ring couplings

Size	Length	Thread	Folded Part #	Price	Coiled Part #	Price
1½"	50'	NST (NH)	R515-50CBF/F	\$240.75	R515-50CBF	\$240.75
1½"	100'	NST (NH)	R515100CBF/F	386.25	R515100CBF	386.25

UL 500# All Polyester Rack Hose - Brass Couplings UL Labeled



folded



coiled

Application:

- for pin rack service / emergency fire fighting only, not to be used for washdown



Features:

- outer construction: single jacket, all polyester
- tube construction: clear thermoplastic
- proof pressure: **300 PSI** at ambient temperature (70°F)
- service test pressure: **150 PSI** at ambient temperature (70°F)
- working pressure: **135 PSI** at ambient temperature (70°F)
- Underwriters Listed

Coupled with female and male brass combo lug expansion ring couplings

Size	Length	Thread	Folded Part #	Price	Coiled Part #	Price
1½"	50'	NST (NH)	R515U50CBF/F	\$269.75	R515U50CBF	\$269.75
1½"	100'	NST (NH)	R515U100CBF/F	467.75	R515U100CBF	467.75

P