

## Miniature Non-Repairable General Purpose Regulators


### Features:

- pressure range 5-125 PSI
- lightweight construction
- left to right flow
- wrench flats for easy installation
- relieving piston design allows reduction of downstream pressure when the system is dead-ended
- RG model supplied with a GC620 gauge

### Compact

Port Size	Flow (SCFM)	with Gauge		without Gauge	
		Part #	Price/E	Part #	Price/E
¼"	13	<b>R46-200RG</b>	<b>\$63.85</b>	<b>R46-200R</b>	<b>\$47.15</b>

SCFM ratings at 100 PSIG.



## Series 1 General Regulators

Floating valve pin provides positive seating and dependability. Large diaphragm provides quick response to flow demands and line pressure changes. Balanced valve reduces inlet pressure variations on outlet pressure.

### Features:

- pressure range 5-125 PSI
- inlet pressure: **400 PSI** at ambient temperature (70°F)
- T-handle adjustment
- supplied with GC620 gauge

Port Size	Flow (SCFM)	with Gauge	
		Part #	Price/E
¼"	110	<b>R11-013RG</b>	<b>\$331.05</b>
⅜"	110	<b>R11-037RG</b>	<b>331.05</b>
½"	260	<b>R11-061RG</b>	<b>379.70</b>

SCFM ratings at 150 PSIG.



## Series 1 Manifold Regulators

Manifold up to six regulators on a single air supply. Design allows in-line installation with hex nipple or modular installation with 72 Series accessories (see pages 256-257).


### Features:

- pressure range 5-150 PSI
- inlet pressure: **300 PSI** at ambient temperature (70°F)
- RG models supplied with GC620 gauge

### Sub-Compact

Port Size	Flow (SCFM)	with Gauge		without Gauge	
		Part #	Price/E	Part #	Price/E
¼"	83	<b>R72M-2RG</b>	<b>\$152.70</b>	<b>R72M-2R</b>	<b>\$136.00</b>
⅜"	83	<b>R72M-3RG</b>	<b>156.50</b>	<b>R72M-3R</b>	<b>139.80</b>

SCFM ratings at 150 PSIG.



## Series 1 Cylinder Gas Regulator

### Applications:



UL listed for service with Carbon Dioxide, water, pumped air, Nitrogen, Argon, Helium, Krypton, Neon and Xenon. *Not to be used with flammable gases.*


### Features:

- pressure range 5-125 PSI
- inlet pressure: **3000 PSI** at ambient temperature (70°F)
- relieving type
- two ports for high pressure and two ports for service

Port Size	Flow (SCFM)	without Gauge	
		Part #	Price/E
¼"	10	<b>R83-200R</b>	<b>\$144.00</b>

See pages 256-257 for regulator accessories.

SCFM ratings given at 1000 PSIG inlet pressure.



FRL's are designed for air service only, unless otherwise indicated.