


Air King with Ferrules

Features:

- working pressure: **150 PSI** at ambient temperature (70°F)
- design provides quick, easy and effective coupling of air hose
- interlocking ferrule can be crimped or swaged to achieve maximum coupling sealing and retention with a low profile streamline appearance, for crimp or swage diameter recommendations see page 839
- for air and water service only 



F

Style	Hose OD		Iron		316 Stainless Steel	
	Part #	Price/E	Part #	Price/E	Part #	Price/E
1/2"	54/64"	1-2/64"	AM1WF	\$14.85	---	---
3/4"	1-4/64"	1-22/64"	AM6WF	12.45	RAM6WF	\$64.00
1"	1-18/64"	1-34/64"	AM11WF-1	22.00	---	---
1"	1-30/64"	1-46/64"	AM11WF	16.50	---	---

Air King with Gauge Port

Features:


- drilled with 1/4" NPT port for mounting a gauge
- gauge sold separately



Size	Iron		316 Stainless Steel	
	Part #	Price/E	Part #	Price/E
3/4"	AM7T	\$24.30	RAM7T	\$76.00

Air King Universal Swivels

Features:

- working pressure: **150 PSI** at ambient temperature (70°F)
- interchanges with other Air King fittings
- includes a heavy-duty, free-turning joint that swivels under pressure to prevent hose kinking
- for air and water service only 



hose end



male NPT



female NPT

Style	Iron		Iron		Iron	
	Part #	Price/E	Part #	Price/E	Part #	Price/E
1/2"	---	---	AM2SWIV	\$63.75	---	---
3/4"	AM6SWIV	\$73.90	AM7SWIV	61.40	AM8SWIV	\$64.65



Air King is for air and water service only *Warning: Never use any Air King coupling for steam service!* None of Dixon's catalog information is to be interpreted to mean that this type of coupling is suitable for use on steam hose.

Compressor Y

Application:

- converts a single supply source to a dual outlet



Female NPT Inlet (1)	Male NPT Outlets (2)	Iron	
		Part #	Price/E
1"	3/4"	Y10075	\$59.75