TYPE BEGCFD, BECCFD, BECSFD

(SP

F1



APPLICATIONS:

- Fans & Blowers
- Pumps
- Compressors

Farm EquipmentMachine Tools

FEATURES:

	1/3 - 10 hp
	1800 RPM
	Totally Enclosed Fan Cooled (IP44)
l	High Torque Design
	36 Month Warranty from Date of Manufacture
	I Phase – 60 Hz – 115/230V (3 hp and Larger are 230V Only)
	Capacitor Start, Induction Run – 1/3 to 1.5 hp
	Capacitor Start, Permanent Split Capacitor Run – 2 to 10 hp
	1.15 Service Factor – Continuous
	Class B Insulation from 1/3 to 3 hp
	Class F Insulation from 5 to 10 hp
	Manual Reset Overload with Outside Rubber Boot
	Class B Temperature Rise
	Bidirectional Rotation
	Rolled Steel Frame for 1/3 – 1 hp
	Cast Iron Frame for 1.5 – 10 hp
	Rolled Steel Terminal Box
	1045 Carbon Steel Shaft
	Aluminum Die Cast Squirrel Cage Rotor Construction
	Paint System: Phenolic Rust Proof Base Plus Polyurethane Top Coat
	Paint Color: Green – Munsell 5G 4/ 4
	Double Shielded Bearings Pre-Packed with MULTEMP SRL Grease
	Rubber Flinger on Drive-End
	Grounding Terminal Inside Main Box
	Stainless Steel Nameplate on Frames 143T and Larger
	Motors are UL Recognized and CSA Approved

EXTRAS/ OPTIONS:

Please <u>click here</u> for a list of common modifications that can be performed.