







SystemOne Recessed 6 Inch Sub-Plates, for Use In Concrete Floors

60/40 Device Plate Combination




- Allows for up to twelve data/AV jacks plus a 20A duplex receptacle
- Two plates which can be wired independently



Left 60% Sub-Plates

Description/Cat. No.	Sub-plate	Description/Cat. No.	Sub-plate
(2) Style Line® Decorator openings, left side only		(1) Style Line® Decorator and (2) 1.5 unit Hubbell iSTATION openings, left side only	
S1R6SPT		S1R6SPU	
(1) Style Line® Decorator and (2) Extron® MAAP openings, left side only		(2) Style Line® Decorator openings, left side only	
S1R6SPV		S1R6SPW	
(1) Style Line® Decorator and (2) Extron® AAP openings, left side only		(1) Style Line® Decorator and (2) 1.5 unit Hubbell iSTATION openings, left side only (See section W for modules)	
S1R6SPX		S1R6SPY	

Right 40% Sub-Plates

(2) 20A pre-wired receptacles; 16 inch lead; one circuit, right side only (Supplied with isolated ground sticker)		(2) 20A pre-wired receptacles; 25 foot lead; one circuit, right side only (Supplied with isolated ground sticker)	
S1R6SPZ		S1R6SPZ25	
(2) 20A pre-wired receptacles; 16 inch lead; one circuit, right side only (Supplied with isolated ground sticker); Marked with "UL Controlled"			
S1R6SPZC			










Note: Sub-plates can not be rotated to create additional layouts. When assembled, sub-plates can not overlap. Custom Plates available upon request and may be subject to minimum order quantity. See page P-12 for Covers and Accessories.

50/50 Device Plate Combination







- Allows for up to eight Hubbell data jacks plus two 20A duplex receptacles
- Two plates which can be wired independently



Left 50% Sub-Plates

Description/Cat. No.	Sub-plate	Description/Cat. No.	Sub-plate
(3) Extron® AAP plate openings, left side only		Blank cover plate, left side only	
S1R6SPA		S1R6SPB	
(5) Extron® MAAP plate openings, left side only		(4) 1 unit Hubbell iSTATION openings, left side only (See section W for modules)	
S1R6SPC		S1R6SPD	
(1) Style Line® Decorator and (2) Hubbell keystone openings, left side only		(2) 1.5 unit Hubbell iSTATION openings, left side only (See section W for modules)	
S1R6SPE		S1R6SPF	
(3) Extron® MAAP openings and (2) Hubbell keystone jack openings, left side only		(1) Style Line® Decorator opening, left side only	
S1R6SPL		S1R6SPM	
(1) Decorator opening and (2) Ortronics® TracJack® openings, left side only			
S1R6SPN			

Right 50% Sub-Plates

(1) Duplex device opening, right side only		(1) Style Line® Decorator device opening, right side only	
S1R6SPI		S1R6SPK	
(1) 1.60 inch opening for 20A and 30A Twist-Lock®, right side only		(1) 1.40 inch opening for simplex or 15A Twist-Lock®, right side only	
S1R6SPG		S1R6SPJ	
(4) 20A pre-wired receptacles; one or two circuits, right side only (Supplied with isolated ground sticker)		(4) 20A pre-wired receptacles; 16 Inch leads; one or two circuits, right side only; Marked with "UL Controlled"	
S1R6SPH (16 Inch leads)		S1R6SPHC4 (4 Controlled)	
S1R6SPH25 (25 Inch leads)		S1R6SPHC2 (2 Controlled)	

Extron® is a registered trademark of Extron Electronics.
TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.