





Duty: Standard
Rolling Elements: Ball
Housing: Cast Iron Piloted Flange Cartridge
Self Alignment: +/- 2 Degrees
Lock: SKWEZLOC Locking Collar
Seal: Felt
Optional Seal: Contact
Temperature: -20° to 220°F



SFC-T Series Standard Duty Piloted Flange Cartridge- SKWEZLOC Locking Collar - Inch

Bore Diameter inch	Part No.	Bearing Insert No.	Basic Dynamic Rating lb/N	Dimensions inch / mm										Bolt Size	Unit Wt. lb/kg
				A	BC	D	G	H	J	L	N	O	P		
1 1/8	SFC-18T	2-12T	4381	4 3/8	3 5/8	1 3/16	3/8	1 3/8	1 5/8	2 3/16	5/8	1/4	3.000	5/16	3.2
1 3/16	SFC-19T	2-13T	19487	111.1	92.1	30.2	9.5	34.9	41.3	55.6	15.9	6.4	76.200		1.45
1 1/4	SFC-20T	2-14T	5782	5	4 1/8	1 5/16	3/8	1 3/8	1 3/4	2 7/16	11/16	3/8	3.375	3/8	4.2
			25718	127.0	104.8	33.3	9.5	34.9	44.5	61.9	17.5	9.5	85.725		1.91
1 3/8	SFC-22T	2-16T	5782	5	4 1/8	1 5/16	3/8	1 3/8	1 3/4	2 9/16	11/16	3/8	3.375	3/8	4.2
1 7/16	SFC-23T	2-17T	25718	127.0	104.8	33.3	9.5	34.9	44.5	65.1	17.5	9.5	85.725		1.91
1 1/2	SFC-24T	2-18T	7340	5 1/4	4 3/8	1 25/64	7/16	1 9/16	2	2 11/16	3/4	7/16	3.625	3/8	5.0
1 9/16	SFC-25T	2-19T	32648	133.4	111.1	35.3	11.1	39.7	50.8	68.3	19.1	11.1	92.075		2.27
1 5/8	SFC-26T	2-110T	7901	6 1/8	5 1/8	1 7/16	7/16	1 9/16	2	2 13/16	3/4	7/16	4.250	7/16	6.3
			35144	155.6	130.2	36.5	11.1	39.7	50.8	71.4	19.1	11.1	107.950		2.86
1 11/16	SFC-27T	2-111T	7901	6 1/8	5 1/8	1 7/16	7/16	1 9/16	2	2 15/16	3/4	7/16	4.250	7/16	6.3
1 3/4	SFC-28T	2-112T	35144	155.6	130.2	36.5	11.1	39.7	50.8	74.6	19.1	11.1	107.950		2.86
1 15/16	SFC-31T	2-115T	7889	6 1/8	5 1/8	1 15/32	7/16	1 5/8	2 3/32	3 3/8	3/4	15/32	4.250	7/16	7.1
2	SFC-32RT	1-2T	35090	155.6	130.2	37.3	11.1	41.3	53.2	85.7	19.1	11.9	107.950		3.22
2	SFC-32T	2-2T	9752	6 3/8	5 3/8	1 19/32	7/16	1 5/8	2 1/4	3 1/2	7/8	5/8	4.500	7/16	8.1
			43377	161.9	136.5	40.5	11.1	41.3	57.2	88.9	22.2	15.9	114.300		3.67
2 1/8	SFC-34T	2-22T	9752	6 3/8	5 3/8	1 19/32	7/16	1 5/8	2 1/4	3 5/8	7/8	5/8	4.500	7/16	8.1
2 3/16	SFC-35T	2-23T	43377	161.9	136.5	40.5	11.1	41.3	57.2	92.1	22.2	15.9	114.300		3.67
2 1/4	SFC-36T	2-24T	11789	7 1/8	6	1 25/32	1/2	1 3/4	2 5/8	4 1/16	1	7/8	5.000	1/2	11.7
			52437	181.0	152.4	45.2	12.7	44.5	66.7	103.2	25.4	22.2	127.000		5.31
2 3/8	SFC-38T	2-26T	11789	7 1/8	6	1 25/32	1/2	1 3/4	2 5/8	4 1/8	1	7/8	5.000	1/2	11.7
2 7/16	SFC-39T	2-27T	52437	181.0	152.4	45.2	12.7	44.5	66.7	104.8	25.4	22.2	127.000		5.31

SFC-T Series Standard Piloted Flange Cartridge - SKWEZLOC Locking Collar - Metric -SKWEZ™

Bore Diameter mm	Part No.	Bearing Insert No.	Basic Dynamic Rating N/lb	Dimensions mm / inch										Bolt Size	Unit Wt. kg/lb
				A	BC	D	G	H	J	L	N	O	P		
30	SFC-206TMC	5206TMC	19487	111.1	92.1	30.2	9.5	34.9	41.3	55.6	15.9	6.4	76.200	M10	1.45
			4381	4 3/8	3.625	1 3/16	3/8	1 3/8	1 5/8	2 3/16	.63	1/4	3.000		3.2
35	SFC-207TMC	5207TMC	25718	127.0	104.8	33.3	9.5	34.9	44.5	61.9	17.5	9.5	85.725	M12	1.91
			5782	5	4.125	1 5/16	3/8	1 3/8	1 3/4	2 7/16	.69	3/8	3.375		4.2
40	SFC-208TMC	5208TMC	32648	133.4	111.1	35.3	11.1	39.7	50.8	68.3	19.1	11.1	92.075	M12	2.27
			7340	5 1/4	4.375	1 25/64	7/16	1 9/16	2	2 11/16	.75	7/16	3.625		5
45	SFC-209TMC	5209TMC	35144	155.6	130.2	36.5	11.1	39.7	50.8	74.6	19.1	11.1	107.950	M14	2.86
			7901	6 1/8	5.125	1 7/16	7/16	1 9/16	2	2 15/16	.75	7/16	4.250		6.3
50	SFC-210TMC	5210TMC	35090	155.6	130.2	37.3	11.1	41.3	53.2	85.7	19.1	11.9	107.950	M14	3.22
			7889	6 1/8	5.125	1 15/32	7/16	1 5/8	2 3/32	3 3/8	.75	15/32	4.250		7.1
55	SFC-211TMC	5211TMC	43377	161.9	136.5	40.5	11.1	41.3	57.2	92.1	22.2	15.9	114.300	M14	3.67
			9752	6 3/8	5.375	1 19/32	7/16	1 5/8	2 1/4	3 5/8	.88	5/8	4.500		8.1
60	SFC-212TMC	5212TMC	52437	181.0	152.4	45.2	12.7	44.5	66.7	104.8	25.4	22.2	127.000	M16	5.31
			11789	7 1/8	6	1 25/32	1/2	1 3/4	2 5/8	4 1/8	1	7/8	5.000		11.7

For Medium Duty SKWEZLOC Locking Collar Bearing Inserts see page G-93.