



Straight Blade Devices




15 and 20 Ampere, 125 Volts




SNAP53621A




SNAP5362LATRA



SNAP5362L



SNAP5362GYLTRA




SNAP52611

Dimensions in Inches (mm)

Extra Heavy Duty SNAPConnect® Receptacles

Duplex

Description	Color	Catalog Number	
Specification grade, finder groove, nylon face, modular receptacle which requires pigtailed connector on page A-15.	Black	SNAP5262BKA	SNAP5362BKA
	Brown	SNAP5262A	SNAP5362A
	Gray	SNAP5262GYA	SNAP5362GYA
	Ivory	SNAP5262IA	SNAP5362IA
	Light Almond	SNAP5262LAA	SNAP5362LAA
	Red	SNAP5262RA	SNAP5362RA
Specification grade, smooth, nylon face, modular receptacle which requires pigtailed connector on page A-15. Assembled in USA.	White	SNAP5262WA	SNAP5362WA
	Black	SNAP5262BKNA	SNAP5362BKNA
	Brown	SNAP5262NA	SNAP5362NA
	Gray	SNAP5262GYNA	SNAP5362GYNA
	Ivory	SNAP5262INA	SNAP5362INA
	Light Almond	SNAP5262LANA	SNAP5362LANA
Specification grade, Tamper-Resistant, smooth nylon face, modular receptacle which requires pigtailed connector on page A-15. Assembled in USA.	Red	SNAP5262RNA	SNAP5362RNA
	White	SNAP5262WNA	SNAP5362WNA
	Black	SNAP5262BKTRA	SNAP5362BKTRA
	Blue	SNAP5262BLTRA	SNAP5362BLTRA
	Brown	SNAP5262TRA	SNAP5362TRA
	Gray	SNAP5262GYTRA	SNAP5362GYTRA
Specification grade, Tamper-Resistant, Split Circuit, smooth nylon face, modular receptacle which requires pigtailed connector on page A-15. Assembled in USA.	Ivory	SNAP5262ITRA	SNAP5362ITRA
	Light Almond	SNAP5262LATRA	SNAP5362LATRA
	Red	SNAP5262RTRA	SNAP5362RTRA
	White	SNAP5262WTRA	SNAP5362WTRA
	Black	SNAP5262BKSCTRA	SNAP5362BKSCTRA
	Blue	SNAP5262BLSCTRA	SNAP5362BLSCTRA
Specification grade, with Power Indicating LED, smooth nylon face, modular receptacle which requires pigtailed connector on page A-15. Assembled in USA.	Brown	SNAP5262SCTRA	SNAP5362SCTRA
	Gray	SNAP5262GYSCTRA	SNAP5362GYSCTRA
	Ivory	SNAP5262ISCTRA	SNAP5362ISCTRA
	Light Almond	SNAP5262LASCTRA	SNAP5362LASCTRA
	Red	SNAP5262RSCTRA	SNAP5362RSCTRA
	White	SNAP5262WSCTRA	SNAP5362WSCTRA
Isolated ground ^A , Specification grade, Tamper-Resistant.	Orange	SNAP5262IGTRA	SNAP5362IGTRA
Specification grade, with Power Indicating LED, smooth nylon face, modular receptacle which requires pigtailed connector on page A-15. Assembled in USA.	Black	SNAP5262BKL	SNAP5362BKL
	Blue	SNAP5262BLL	SNAP5362BLL
	Brown	SNAP5262L	SNAP5362L
	Gray	SNAP5262GYL	SNAP5362GYL
	Ivory	SNAP5262IL	SNAP5362IL
	Light Almond	SNAP5262LAL	SNAP5362LAL
Specification grade, Tamper-Resistant, with Power Indicating LED, smooth nylon face, modular receptacle which requires pigtailed connector on page A-15. Assembled in USA.	Red	SNAP5262RL	SNAP5362RL
	White	SNAP5262WL	SNAP5362WL
Isolated ground ^A , Specification grade, with Power Indicating LED.	Orange	SNAP5262IGL	SNAP5362IGL
Specification grade, Tamper-Resistant, with Power Indicating LED, smooth nylon face, modular receptacle which requires pigtailed connector on page A-15. Assembled in USA.	Black	SNAP5262BKLTRA	SNAP5362BKLTRA
	Blue	SNAP5262BLLTRA	SNAP5362BLLTRA
	Brown	SNAP5262LTRA	SNAP5362LTRA
	Gray	SNAP5262GYLTRA	SNAP5362GYLTRA
	Ivory	SNAP5262ILTRA	SNAP5362ILTRA
	Light Almond	SNAP5262LALTRA	SNAP5362LALTRA
Isolated ground ^A , Specification grade, TR with Power Indicating LED.	Red	SNAP5262RLTRA	SNAP5362RLTRA
	White	SNAP5262WLTRA	SNAP5362WLTRA
	Orange	SNAP5262IGLTRA	SNAP5362IGLTRA



SNAPConnect® Extra Heavy Duty Standard Single Receptacles

Color	Standard Duplex		Standard Duplex Tamper-Resistant	
	15A 125V	20A 125V	15A 125V	20A 125V
Almond	SNAP5261AL	SNAP5361AL	SNAP5261ALTR	SNAP5361ALTR
Black	SNAP5261BK	SNAP5361BK	SNAP5261BKTR	SNAP5361BKTR
Blue	SNAP5261BL	SNAP5361BL	SNAP5261BLTR	SNAP5361BLTR
Brown	SNAP5261	SNAP5361	SNAP5261TR	SNAP5361TR
Gray	SNAP5261GY	SNAP5361GY	SNAP5261GYTR	SNAP5361GYTR
Ivory	SNAP5261I	SNAP5361I	SNAP5261ITR	SNAP5361ITR
Light Almond	SNAP5261LA	SNAP5361LA	SNAP5261LATR	SNAP5361LATR
Red	SNAP5261R	SNAP5361R	SNAP5261RTR	SNAP5361RTR
White	SNAP5261W	SNAP5361W	SNAP5261WTR	SNAP5361WTR