

Nickel Plated 4-Bolt Flanges





**With optional bearing inserts:
Stainless Steel-SUCNPF
Hard Chrome Coated-CUCNPF**

- B-type seals
- Available with locking collar bearings. Please ask.
- Overview of corrosion resistant products – pg. 48



B-type Seal



CORROSION RESISTANT

Unit No.	Shaft Dia.		Dimensions (in. (mm))										Bolt Used (in.)	Bearing No.	Housing No.	Weight (lbs.)
	d (in.)	d (mm)	A	E	I	G	L	S	Z	Bi	N	M				

SUCNPF with Stainless Steel Bearing Inserts

SUCNPF 201-8	1/2															SUC 201-8		
202-10	5/8		3 3/8	2 1/2	1 9/32	7/16	1	7/16	1 5/16	1.2205	0.5000	0.7205	3/8	SUC 202-10				
204-12	3/4		86	64	15	11	25.4	11	33.3	31.0	12.7	18.3		204-12	NPF 204	1.4		
204		20																
SUCNPF 205-14	7/8															SUC 205-14		
205		25	3 3/4	2 3/4	5/8	1/2	11/16	2 9/64	1 13/32	1.3386	0.5630	0.7756	3/8	205	NPF 205	1.9		
205-16	1		95	70	16	13	27	11.5	35.7	34.0	14.3	19.7		205-16				
SUCNPF 206-18	1 1/8															SUC 206-18		
206		30	4 1/4	3 1/4	45/64	1/2	17/32	33/64	1 19/32	1.5000	0.6260	0.8740	7/16	206	NPF 206	2.4		
206-19	1 3/16		108	83	18	13	31	13	40.2	38.1	15.9	22.2		206-19				
206-20	1 1/4 S													206-20				
SUCNPF 207-20	1 1/4															SUC 207-20		
207-21	1 5/16															207-21		
207-22	1 3/8		4 19/32	3 5/8	3/4	1 9/32	1 11/32	33/64	1 3/4	1.6890	0.6890	1.0000	7/16	207-22	NPF 207	3.3		
207		35	117	92	19	15	34	13	44.4	42.9	17.5	25.4		207				
207-23	1 7/16													207-23				
SUCNPF 208-24	1 1/2															SUC 208-24		
208		40	5 1/8	4	53/64	1 9/32	1 13/32	35/64	2 1/32	1.9370	0.7480	1.1890	1/2	208	NPF 208	4.2		
SUCNPF 209-27	1 11/16															SUC 209-27		
209-28	1 3/4		5 13/32	4 1/8	55/64	5/8	1 1/2	5/8	2 1/16	1.9370	0.7480	1.1890	9/16	209-28	NPF 209	5.2		
209		45	137	105	22	16	38	16	52.2	49.2	19.0	30.2		209				
SUCNPF 210-31	1 15/16															SUC 210-31		
210		50	5 5/8	4 3/8	55/64	5/8	1 9/16	5/8	2 5/32	2.0315	0.7480	1.2835	9/16	210	NPF 210	5.6		
210-32	2 S		143	111	22	16	40	16	54.6	51.6	19.0	32.6		210-32				
SUCNPF 211-32	2															SUC 211-32		
211-35	2 3/16		6 3/8	5 1/8	63/64	23/32	1 11/16	43/64	2 5/16	2.1890	0.8740	1.3150	5/8	211-35	NPF 211	7.7		
SUCNPF 212-36	2 1/4															SUC 212-36		
212-39	2 1/16		6 7/8	5 5/8	1 9/64	23/32	1 7/8	43/64	2 23/32	2.5630	1.0000	1.5630	5/8	212-39	NPF 212	9.4		

CUCNPF with Hard Chrome Coated Bearing Inserts

CUCNPF 204-12	3/4															CUC 204-12		
204		20	3 3/8	2 1/2	1 9/32	7/16	1	7/16	1 5/16	1.2205	0.5000	0.7205	3/8	204	NPF 204	1.4		
CUCNPF 205-14	7/8															CUC 205-14		
205		25	3 3/4	2 3/4	5/8	1/2	11/16	2 9/64	1 13/32	1.3386	0.5630	0.7756	3/8	205	NPF 205	1.9		
205-16	1		95	70	16	13	27	11.5	35.7	34.0	14.3	19.7		205-16				
CUCNPF 206-18	1 1/8															CUC 206-18		
206		30	4 1/4	3 1/4	45/64	1/2	17/32	33/64	1 19/32	1.5000	0.6260	0.8740	7/16	206	NPF 206	2.4		
206-19	1 3/16		108	83	18	13	31	13	40.2	38.1	15.9	22.2		206-19				
206-20	1 1/4 S													206-20				
CUCNPF 207-20	1 1/4															CUC 207-20		
207-22	1 3/8		4 19/32	3 5/8	3/4	1 9/32	1 11/32	33/64	1 3/4	1.6890	0.6890	1.0000	7/16	207-22	NPF 207	3.3		
207		35	117	92	19	15	34	13	44.4	42.9	17.5	25.4		207				
207-23	1 7/16													207-23				
CUCNPF 208-24	1 1/2															CUC 208-24		
208		40	5 1/8	4	53/64	1 9/32	1 13/32	35/64	2 1/32	1.9370	0.7480	1.1890	1/2	208	NPF 208	4.2		
CUCNPF 209-27	1 11/16															CUC 209-27		
209-28	1 3/4		5 13/32	4 1/8	55/64	5/8	1 1/2	5/8	2 1/16	1.9370	0.7480	1.1890	9/16	209-28	NPF 209	5.2		
209		45	137	105	22	16	38	16	52.2	49.2	19.0	30.2		209				
CUCNPF 210-31	1 15/16															CUC 210-31		
210		50	5 5/8	4 3/8	55/64	5/8	1 9/16	5/8	2 5/32	2.0315	0.7480	1.2835	9/16	210	NPF 210	5.6		
210-32	2 S		143	111	22	16	40	16	54.6	51.6	19.0	32.6		210-32				
CUCNPF 211-32	2															CUC 211-32		
211-35	2 3/16		6 3/8	5 1/8	63/64	23/32	1 11/16	43/64	2 5/16	2.1890	0.8740	1.3150	5/8	211-35	NPF 211	7.7		
CUCNPF 212-36	2 1/4															CUC 212-36		
212-39	2 1/16		6 7/8	5 5/8	1 9/64	23/32	1 7/8	43/64	2 23/32	2.5630	1.0000	1.5630	5/8	212-39	NPF 212	9.4		
CUCNPF 213-40	2 1/2															CUC 213-40		
213-40			187	143	30	22	50	17	69.7	65.1	25.4	39.7		213-40	NPF 213	12.9		
CUCNPF 215-47	2 15/16															CUC 215-47		
215-48	3		7 7/8	6 1/4	1 11/32	7/8	2 1/2	3/4	3 3/32	3.0630	1.3110	1.7520	1 1/16	215-48	NPF 215	15.0		