

## Horizontal Swing Check Valves

### Application:

- Swing check valves are designed to prevent back flow in plumbing and liquid piping systems, while offering full flow performance with a minimum of turbulence or pressure loss.

### Features:

- brass disc
- for horizontal or vertical use
- A positive seating disc allows flow only in one direction and a screw-in cap provides easy access for periodic cleaning.
- pressure rating: **200 PSI** WOG
- temperature range: **-20° to 150°F**



### female NPT x female NPT

Size	Brass	
	Part #	Price/E
1/2"	<b>SWCV50</b>	<b>\$19.90</b>
3/4"	<b>SWCV75</b>	<b>26.10</b>
1"	<b>SWCV100</b>	<b>35.55</b>
1 1/4"	<b>SWCV125</b>	<b>56.50</b>
1 1/2"	<b>SWCV150</b>	<b>71.10</b>
2"	<b>SWCV200</b>	<b>110.80</b>
3"	<b>SWCV300</b>	<b>309.80</b>
<b>NEW</b> 4"	<b>SWCV400</b>	<b>440.00</b>

## Domestic Swing Check Valves

### Features:

- Class 150
- ASME B1.20.1
- metal seat
- 100% factory tested
- working pressure: **300 PSI** cold, **150 PSI** steam
- temperature range: **-20°F to 406°F**



Female NPT	Brass	
	Part #	Price/E
1/2"	<b>DSCV50</b>	<b>\$146.10</b>
3/4"	<b>DSCV75</b>	<b>177.45</b>
1"	<b>DSCV100</b>	<b>238.60</b>
1 1/4"	<b>DSCV125</b>	<b>316.10</b>
1 1/2"	<b>DSCV150</b>	<b>410.05</b>
2"	<b>DSCV200</b>	<b>612.90</b>

## Cast Iron Y Line Strainers

### Features:

- cast iron body
- graphite gasket
- working pressure: **400 PSI** WOG, **250 PSI** steam
- plug ported for blowdown service
- no replacement screens available

products used with the strainer:

- MNPT threaded close nipples, page 730
- brass ball valves, page 668
- MNPT threaded plugs, page 724



Female NPT	Description	Cast Iron	
		Part #	Price/E
1/4"	20 x 20 mesh	<b>Y001</b>	<b>\$28.30</b>
3/8"	20 x 20 mesh	<b>Y002</b>	<b>28.30</b>
1/2"	20 x 20 mesh	<b>Y003</b>	<b>33.95</b>
3/4"	20 x 20 mesh	<b>Y004</b>	<b>41.50</b>
1"	20 x 20 mesh	<b>Y005</b>	<b>51.85</b>
1 1/4"	20 x 20 mesh	<b>Y006</b>	<b>73.45</b>
1 1/2"	20 x 20 mesh	<b>Y007</b>	<b>90.45</b>
2"	20 x 20 mesh	<b>Y008</b>	<b>135.65</b>