


Strainer with Spring-Loaded Check Valves

Features:

- brass with NBR seat and stainless steel strainer
- soft seat for bubble tight shutoff, spring loaded for fast seating action
- flow profile designed to minimize head loss
- temperature range: **10°F to 210°F (-10°C to 100°C)**
- cracking pressure: **0.50 PSI**
- pressure rating: **1½"-2" 400 PSI WOG, 3"-4" 175 PSI WOG**



Female NPT	Brass	
	Part #	Price/E
1½"	BVFS20	\$89.60
2"	BVFS25	129.00
3"	BVFS35	379.50
4"	BVFS40	572.50

Horizontal Swing Check Valves

Applications:

- for use in plumbing and liquid piping systems to prevent back flow

Features:

- full flow performance with a minimum of turbulence or pressure loss
- brass disc
- for horizontal or vertical use
- A positive seating disc allows flow only in one direction and a screw-in cap provides easy access for periodic cleaning.
- pressure rating: **200 PSI WOG**
- temperature range: **-20° to 150°F (-29°C to 66°C)**




Female NPT	Brass	
	Part #	Price/E
½"	SWCV50	\$19.90
¾"	SWCV75	26.10
1"	SWCV100	35.55
1¼"	SWCV125	56.50
1½"	SWCV150	71.10
2"	SWCV200	110.80
3"	SWCV300	309.80
4"	SWCV400	440.00

Domestic Swing Check Valves

Features:

- Class 150
- ASME B1.20.1
- metal seat
- 100% factory tested
- working pressure: **300 PSI cold, 150 PSI steam**
- temperature range: **-20°F to 406°F (-29°C to 208°C)**



Female NPT	Brass	
	Part #	Price/E
½"	DSCV50	\$154.00
¾"	DSCV75	187.00
1"	DSCV100	252.00
1¼"	DSCV125	333.00
1½"	DSCV150	432.00
2"	DSCV200	646.00