

Sprinkler System Gauge (UL-393)



Features:

- specifically designed for the fire sprinkler industry
- Bourdon tube pressure gauges with black polycarbonate case
- snap-in clear polycarbonate window, 4" face
- white aluminum dial with stop pin, black and red markings
- black aluminum non-adjustable pointer
- 1/4" NPT lower mount
- ASME B40.1 Grade B (+ 3/2/3% accuracy)
- U/L Listed (U/L-393) and Factory Mutual Approved for fire sprinkler service
- temperature range: -40°F to 140°F (-40°C to 60°C)



Maintenance
& Repair

Type	Part #	Price/E
water (0-300 PSI)	SWG300-4	\$38.40

Line Test Gauges

Features:

- rocker lug swivel
- used for testing static or flowing pressures in hoses or nozzles
- supplied with **0-300 PSI** glycerine filled 3 1/2" diameter gauge
- freeze proof to -40°F (-40°C)
- other sizes and threads are also available, contact Dixon®



NST (NH) Thread	Hardcoated Aluminum	
	Part #	Price/E
1 1/2"	ALTG150F	\$446.30
2 1/2"	ALTG250F	330.00

Three Way Gauge Valve

Features:

- permits checking or replacing a gauge without shutting down the whole line
- disc: rubber



NPT Thread	Working Pressure (PSI)	Part #	Brass	Price/E
1/4"	175	TWGV25		\$22.10

PITOT Gauge

Features:

- liquid filled gauge 0-160 PSI is standard, other pressures available, contact Dixon®
- supplied with handle grip, case and fire stream/friction loss data



Part #	Price/E
PG8083	\$536.80

Sprinkler Line Tester

Feature:

- installs on the last sprinkler head on system branch lines and controls water flow for flushing or testing the system



Inlet	Outlet	Part #	Brass	Price/E
1" female NPT	1" male NPSH	SLT10050		\$112.75