



## U/L Play Pipes with Tip

**Application:**

- often required in hydrant houses by Insurance Underwriters

**Features:**

- swivel handle, red marlin trim
- maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)
- U/L listed and Factory Mutual approved
- ULT male thread specification: 2-3/16" ODM x 12 TPI
- comes standard with 1-1/8" orifice tip

Size	Female	Male	OAL	Brass		Wt. Lbs.
				Part #	Price/E	
2½"	NST (NH)	ULT	30"	<b>UPP250F</b>	<b>\$718.35</b>	9
2½"	NPSH	ULT	30"	<b>UPP250S</b>	<b>718.35</b>	9

## Tips for U/L Play Pipe

**Features:**

- finish: satin
- maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)
- ULT male thread specification: 2-3/16" ODM x 12 TPI



Orifice	Cast Brass		Wt. Lbs.
	Part #	Price/E	
1⅛"	<b>UPPT</b>	<b>\$133.00</b>	1.6
1¼"	<b>UPPT125</b>	<b>120.00</b>	1.6
1½"	<b>UPPT150</b>	<b>120.00</b>	1.6
1¾"	<b>UPPT175</b>	<b>135.00</b>	1.6


## Adjust-A-Power Nozzle

**Application:**

- ideal for patio, auto and boat, driveway and garden, can be used as a mop-up nozzle as it produces 50% more power than twist nozzles

**Features:**

- gasketed from inlet to tip it does not leak like conventional nozzles and does not require a washer
- three stainless steel ball bearings in the adjustable tip offer complete shut off, to ultra powerful pinpoint stream, to heavy spray pattern, to a solid jet stream or any setting in between
- leave nozzle in the open position when not in use
- design minimizes water usage and maximizes water velocity
- maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)



Size	Thread	Brass		Wt. Lbs.
		Part #	Price/E	
¾"	GHT	<b>AAPN75GHT</b>	<b>\$24.00</b>	0.2

## Garden Hose Twist Nozzles

**Feature:**

- maximum operating pressure: **150 PSI** (water only)



Size	Thread	Length	Brass		Wt. Lbs.
			Part #	Price/E	
¾"	GHT	4"	<b>BTN75</b>	<b>\$17.90</b>	0.40
¾"	GHT	7"	<b>500-AN7</b>	<b>37.98</b>	0.66